## **Drum Machines**





## K-750 DRUM MACHINE

- 3" to 8" (75 to 200 mm) Drain/Sewer Lines
- Recommend 5/8" (16 mm) cable for 3" to 6" (75 to 150 mm) drain lines up to 150' (48 m).
- Recommend ¾" (20 mm) cable for 4" to 8" (100 to 200 mm) drain lines up to 200' (62 m).
- Powerful, self-contained machine ideal for lateral lines. Easy to transport, minimal set-up attach a tool and go.
- AUTOFEED control advances and retrieves cable with a push of a lever, up to 20' (6 m) per minute.
- Versatile AUTOFEED control adjusts for either 5/8" (16 mm) or 3/4" (20 mm) cable with a twist of a screwdriver.
- Tough, corrosion-resistant cable drum withstands harsh treatment and abuse. It will not dent or corrode and cleans easily.
- Drum holds 100' (30.5 m) of ¾" (20 mm) or 125' (35 m) of ¾" (16 mm) cable and is designed for quick, easy removal.
- Balanced design gives the machine a lightweight "feel." Transport wheels ease loading into service truck/van.
- Equipped with 1/2 HP induction motor that spins cable at 200 RPM.
- Includes RIDGID® PVC drain cleaning gloves and operators manual.

## **Machine Options**

Catalog	Madel No	Decayinting	Voltage	Weight	
No.	Model No.	Description	V	lb.	kg
41977	K-750	Machine with Gloves and AUTOFEED - 3/4" (20 mm) Pigtail	115	114	51.9
51402	N-730	Machine with Gloves and AUTOFEED - 5/8" (16 mm) Pigtail	115	113	51.3
42002	K-750 with C-75	Machine with One Pair of Gloves, AUTOFEED, Standard 3/4" (20 mm) Tool Set, and: C-75, 75' (23 mm) x 3/4" (20 mm) Cable		206	93.6
42007	K-750	Machine with One Pair of Gloves, w/C-100 AUTOFEED, Standard 3/4" (20 mm) Tool Set, and: C-100, 100' (30.5 mm) x 3/4" (20 mm) Cable	115	234	106.3
42012	K-750 with C-27	Machine with One Pair of Gloves, AUTOFEED, Standard <sup>5</sup> / <sub>8</sub> " (16 mm) Tool Set, and: C-27, 75' (23 mm) x <sup>5</sup> / <sub>8</sub> " (16 mm) Cable		182	82.7
47047	K-750 with C-24	Machine with One Pair of Gloves, AUTOFEED, Standard 5/s" (16 mm) Tool Set, and: C-24, 100' (30.5 mm) x 5/s" (16 mm) Cable	115	102	02.1
44202		Machine with Gloves and AUTOFEED - 3/4" (20 mm) Pigtail	230	114	51.9
51407	K-750	Machine with Gloves and AUTOFEED - 5/8" (16 mm) Pigtail	230	113	51.3
44212	N-750	Machine with One Pair of Gloves, w/C-100 AUTOFEED, Standard 3/4" (20 mm) Tool Set, and: C-100, 100' (30.5 mm) x 3/4" (20 mm) Cable	230	234	106.3
44217	K-750 with C-27	Machine with One Pair of Gloves, AUTOFEED, Standard 5/8" (16 mm) Tool Set, and: C-27, 75' (23 mm) x 5/8" (16 mm) Cable	230	182	82.7

## Standard Equipment

Catalog No. Model No.	Description	41977 K-750	51402 K-750	42002 K-750 w/C-75	42007 K-750	42012 K-750 w/C-27	47047 K-750 w/C-24	44202 K-750	51407 K-750		44217 K-750 w/C-27
41937	RIDGID Leather Drain Cleaning Gloves	ı	ı	ı	ı	ı	ı	ı	ı	ı	ı
41212	34" (20 mm) x 75' IC Cable (22.9m)			ı							
92495	Spade Cutter, 13/4" (45 mm)			ı	ı	ı	ı			ı	ı
92500	Retrieving Auger 2 %6" (65 mm)			ı	ı	ı	ı			ı	ı
92510	Double Cutter, 2" (50 mm)			ı	ı	ı	ı			ı	ı
92520	Double Cutter, 3" (75 mm)			ı	ı	ı	ı			ı	ı
92525	Double Cutter, 4" (110 mm)			ı	ı					ı	
41697	34" (20 mm) x 100' IC Cable (30.5m)				ı					ı	
92470	<b>5</b> ⁄ <sub>8</sub> " (16 mm) x 75' IC Cable (22.9m)					ı					ı
92485	P-Trap Cutter, 3" (75 mm)					1	ı				ı
43647	<b>5%</b> " (16 mm) x 100' IC Cable (30.5m)						ı				