

INSTALLATION, OPERATION & MAINTENANCE INSTRUCTIONS

1455 Kleppe Lane *Sparks, NV 89431-6467 *(775) 359-4712 *Fax (775) 359-7424 E-mail: haws@hawsco.com * website: www.hawsco.com

No. 2080038(19)

Model 7260B-7270B/7260BT-7270BT Eye/Face Wash

NOTE TO INSTALLER: Please leave this information with the Maintenance Department.

LIMITED WARRANTY

HAWS warrants that this specific product is guaranteed against defective material or poor workmanship for a period of **one year from date of shipment**. HAWS liability under this warranty shall be discharged by furnishing without charge F.O.B. HAWS Factory any goods, or part thereof, which shall appear to the Company upon inspection to be of defective material or not of first class workmanship, provided that claim is made in writing to Haws within a reasonable period after receipt of the product. Where claims for defects are made, the defective part or parts shall be delivered to the Company, prepaid, for inspection. HAWS will not be liable for the cost of repairs, alterations or replacements, or for any expense connected therewith made by the owner or his agents, except upon written authority from HAWS, Sparks, Nevada. HAWS will not be liable for any damages caused by defective materials or poor workmanship, except for replacements, as provided above. Buyer agrees that Haws has made no other warranties either expressed or implied in addition to those above stated, except that of title with respect to any of the products or equipment sold hereunder and that HAWS shall not be liable for general, special, or consequential damages claimed to arise under the contract of sale.

The emergency equipment manufactured by HAWS is warranted to function if installation and maintenance instructions provided are adhered to. The units also must be used for the purpose for which they were intended. This product is intended to supplement first-aid treatment. Due to widely varying conditions, Haws cannot guarantee that the use of this emergency equipment will prevent serious injury or the aggravation of existing or prior injuries.

NO OTHER WARRANTIES EXPRESSED OR IMPLIED ARE AUTHORIZED, PROVIDED OR GIVEN BY HAWS.

SHOULD YOU EXPERIENCE DIFFICULTY WITH THE INSTALLATION OF THIS MODEL PLEASE CALL:

TECHNICAL SUPPORT: 1-800-766-5612

FOR CUSTOMER SERVICE: 1-888-640-4297

LOCATION OF UNIT: The Model 7260B-7270B/7260BT-7270BT Eyewash units should be installed in close proximity to potential accident areas. It should be clearly identified, free from obstructions and easy to access.


SUPPLY LINE: The minimum recommended line size is 1/2" IPS with 30-90 psi (2-6 ATM) flowing pressure. Where sediment or mineral content is a problem, an inlet filter is recommended.

PLUMBING CONNECTIONS: For Model 7260B-7270B/7260BT-7270BT, the inlet supply is female 1/2" NPT. For Model 7260B-7270B, the waste outlet is 1-1/4" NPT. For Model 7260BT-7270BT, the waste outlet is 1-1/2" NPT.

TROUBLESHOOTING				
PROBLEM			REPAIR CHECKLIST	
1.	No flow.	1.		Check the main shut-off valve.
2.	Insufficient water flow.	2.	a.	Verify minimum 30psi flowing supply line pressure.
			b.	Probable clogging of flow control due to inadequate line flushing. Unscrew eye/face wash head and remove the four screws to disassemble the head. Clean flow control and reassemble head. See SP65 Installation Drawing for details.
			c.	Remove cap located on L – Strainer using a 3/8" allen wrench to access and clean filter screen.
3.	Eyewash or face wash streams do not meet desired eye level or are not balanced.	3.		Possible blocked flow control, see above solution. Possible non-leveled eyewash assembly.
4.	Water does not drain properly.	4.		Check the main waste line of your building to see if it does handle the capacity required for the entire drainage system.

For more information about Haws products, see our website: www.hawsco.com

© 2017 Haws® Corporation – All Rights Reserved HAWS® and other trademarks used in these materials are the exclusive property of Haws Corporation.



©2017 Haws Corporation - All Rights Reserved

WHEN ORDERING PARTS PLEASE SPECIFY MODEL NUMBER.

PAGE 3 of 4

0002080038

MODEL(S)

7260B-7270B/7260BT-7270BT

14 1/8 [359]

8 1/2 [216]

COVER


BRACKET FOR OPTIONAL DUST

10 3/8" ±1"

[264] ± [25]

1/2" NPT

SUPPLY



NOTES:

1. WHEN INSTALLING THIS UNIT, LOCAL, STATE, OR FEDERAL CODES SHOULD BE ADHERED TO FOR INSTALLATION DIMENSIONS (LOCATIONS), WASTE AND SUPPLY REQUIREMENTS OTHER THAN SHOWN.

- 2. TO COMPLY WITH ANSI Z358.1-2014 FOR EMERGENCY EYEWASH OR EYE/FACE WASH:
 EYEWASH OR EYE/FACE WASH SHALL BE POSITIONED SUCH THAT FLUSHING FLUID PATTERN IS
 NOT LESS THAN 33" (838mm) AND NO GREATER THAN 53" (1346 mm) FROM SURFACE ON WHICH
 USER STANDS; AND 6.0" (153mm) MINIMUM FROM WALL OR NEAREST OBSTRUCTION.
- 3 HEIGHT IS DETERMINED BY WATER FLOW PATTERN HEIGHT SHOWN, WHICH IN TURN, IS DEPENDENT ON IN-LINE SUPPLY PRESSURE.
- 4. DIMENSIONS MAY VARY BY ±1/2" (13 mm).
- ${\bf 5. \ \, DIMENSIONS \, IN \, BRACKETS, \, IN \, DRAWING \, SPACE, \, \, ARE \, METRIC \, [mm].}$



1455 KLEPPE LANE SPARKS, NEVADA 89431 (775) 359-4712 FAX (775) 359-7424 E-MAIL: HAWS@HAWSCO.COM WEBSITE: WWW.HAWSCO.COM

ECN NO. REVISED PER BY: 4181 | ECN: 5175 | VWC
DRAWN: DATE: CHKD: 7260B-7270B/7260BT-7270BT
SLS 5/1/08 | VWC
DATE: DATE: CHKD: 7260B-7270B/7260BT-7270BT

PART NUMBER 0002080038.D REVISION 19