

# RESPIRATOR LOCKER®

**2250N95** FIVE 2200N95 MASKS

**2350N95** FIVE 2300N95 MASKS

**2850N95** FOUR 2800N95 MASKS

## HANDY TWO IN ONE STORAGE!

Respirator Locker® provides hygienic storage for respirators. It's a personal dispenser for workers required to travel to remote locations. Fits easily in employee lockers or work vehicles. Separate compartment permits storage of a used respirator during breaks, preventing premature disposal.

## LESS WASTE, SAVES MONEY

Reduces employee waste from taking extra respirators for the day. Allows employer to track respirator usage. Saves time going to get fresh respirators. The result is fewer respirators used and lower costs.

## EASY FIT, MORE COMFORT

Each Moldex respirator has our exclusive Dura-Mesh shell that protects the filter media, so it stays cleaner looking longer. The shell resists collapsing, even in heat and humidity so the respirator holds its shape longer. Model #2350N95 and #2850N95 also features an exhale valve that reduces hot air buildup. Workers stay cooler and comfortable longer. In addition Model #2850 has a special carbon layer that helps relieve workers of nuisance levels (less than OSHA PEL) of ozone and organic vapor odors. Suitable for most welding fumes.



*Outer Dura-Mesh keeps respirator cleaner looking*

*Inner Dura-Mesh helps prevent collapsing from heat and humidity*

*Filter is protected on both sides by Dura-Mesh*

*Softspun lining is comfortable against the face*



## FEATURES

- Allows employer to monitor respirator usage, reducing costs.
- Reduces time spent getting new respirators.
- Convenient supply for workers at field worksites.
- Provides each worker with hygienic storage and a personal supply of respirators.
- Separate chamber stores used respirator during breaks.
- Holds four or five masks per Locker.
- HandyStrap® allows mask to conveniently hang down around the user's neck when not in use.
- Locker keeps Model #2850N95 carbon layer fresh.
- Meets heat and flame resistance in accordance with ANSI/ISEA 110-2003 Section 7.11.1.
- 100% PVC-Free.



# RESPIRATOR LOCKER®

**2250N95** FIVE 2200N95 MASKS  
**2350N95** FIVE 2300N95 MASKS  
**2850N95** FOUR 2800N95 MASKS

PART # / DESCRIPTION	SIZE	DISPLAY	CASE
2250N95 Respirator Locker w/ 5 2200N95 Masks	M/L	5/Locker	27 Lockers
2350N95 Respirator Locker w/ 5 2300N95 Masks	M/L	5/Locker	16 Lockers
2850N95 Respirator Locker w/ 4 2800N95 Plus Nuisance OV Masks	M/L	4/Locker	16 Lockers

M/L = Medium/Large

**N95 APPLICATIONS:** Grinding, Torch Cutting, Sanding, Metal Pouring, Sweeping, Metal Working, Bagging, Foundries, Stone Quarrying, Agriculture, Metal Machining, Construction Sites, Cement, Ceramics Manufacturing, Underground Mining, Timber/Lumber Mills, Polishing, Buffing, Lime, Poultry, Textiles, Welding, Brazing, Soldering.

**N95 Plus Nuisance Levels of Ozone and Organic Vapors Applications:** Welding, Arc Cutting, Foundry Operations, Brazing, Plasma Spraying, Laser Beam Cutting/Welding, Laboratory Settings, Agriculture, Petrochemical Manufacturing, Rendering Plants, Auto Repair, Mining Operations, Waste Disposal.

## USE AGAINST (2250N95, 2350N95):

1. Particulate aerosols free of oil.

## USE AGAINST (2850N95):

1. Particulate aerosols free of oil.
2. Nuisance levels (OSHA Permissible Exposure Limits) of Organic Vapor Odors and/or Ozone.

## DO NOT USE AGAINST:

1. Concentrations of contaminants which are unknown, or are immediately dangerous to life or health.
2. Concentrations of particulates which exceed the maximum use concentration or 10 times the OSHA Permissible Exposure Limit, whichever is lower.
3. Gases, vapors, asbestos, paint spray, sandblasting or particulate materials which generate harmful vapors. This respirator is not approved for any vapors or gases, so when used against organic vapor odors and/or ozone do not exceed the OSHA Permissible Exposure Limits.
4. Oil-based mists.

## RESTRICTIONS

1. This respirator does not supply oxygen and must not be used in atmospheres containing less than 19.5% oxygen.
2. Do not remain in contaminated area if any physical distress occurs, for example breathing difficulty, dizziness or nausea.
3. Leave contaminated area and replace respirator if it is damaged, distorted, a proper fit can not be obtained or breathing becomes difficult.
4. Prior to each use, carefully inspect the entire respirator, including filter media and strap/weld attachment area for tears and damage. Staple or strap/weld attachment perforations do not affect respirator performance.
5. Do not alter, modify, or abuse this respirator.
6. Store unused respirators in box/bag in a clean, dry, non-contaminated area.
7. Dispose of respirator according to your employer's policy and local regulations.
8. Dispose no later than thirty days after first use.
9. Use respirator before the "use by" expiration date printed on box/bag.
10. If used for welding, wear appropriate eye and face protection.

## WARNING TO USER

1. Follow all instructions and warnings on the use of this respirator and wear during all times of exposure. Failure to do so will reduce respirator effectiveness, wearer protection and may result in sickness or death.
2. Before use, the user must first be trained by the employer in proper respirator use, in accordance with applicable safety and health standards, for the contaminant and exposure level in the assigned work area.
3. The particulates and other contaminants which can be dangerous to your health include those which you cannot see, taste, or smell.
4. This product has not been sold with warnings or use instructions for personnel involved in healthcare or related situations, where there may be the possibility of contact with disease or biological hazards. If you are considering such uses, first call the Moldex Technical Service Department: +1 (800) 421-0668 or +1 (310) 837-6500 ext. 512/550

## DISTRIBUTED BY:

**MOLDEX-METRIC, INC.**  
10111 West Jefferson Blvd.  
Culver City, CA 90232  
TEL: +1 (800) 421-0668 or +1 (310) 837-6500  
FAX: +1 (310) 837-9563  
E-mail: sales@moldex.com www.moldex.com

**CANADIAN CUSTOMER SERVICE**  
Tel: +1 (800) 421-0668, Ext. 517  
Fax: +1 (310) 837-9563

