

RUST TOUGH® UTILI-COAT™ ENAMEL

Developed for the toughest environments, Utili-Coat's unique, high-solids, direct-to-metal (on new or clean metal) formulation delivers long-lasting performance.

- Premium rust-preventive enamel
- State-of-the-art corrosion protection
- One-coat coverage
- Direct-to-metal, rust-preventive formula — no primer needed
- Equipped with a standard conical actuator
- Excellent gloss and color retention

COLORS	20 oz. (15 oz. net wt.)
Utility Meter Gray (ANSI-49)	K20879007
PRIMERS	20 oz. (15 oz. net wt.)
Gray	K20829007



Case Pack: 6



ACRYLI-QUIK™ ACRYLIC LACQUER

These paints are specifically formulated for industrial maintenance and touch-up applications. Performance is exceptional, and the broad selection includes interior/exterior acrylic lacquers, primers and specialty paints. Acryli-Quik offers high solids, fast-drying times and an excellent appearance. No Runs, No Drips, No Errors!®

- No recoat window — recoat anytime
- Dries to touch in 8 minutes
- Hard, protective, durable finish
- High-gloss finish

COLORS	16 oz. (12 oz. net wt.)	COLORS	16 oz. (12 oz. net wt.)
Sun Yellow	K01806A07	Crystal Clear	K01301A07
Daisy Yellow	K01813A07	Ultra-Flat Black	K01602A07
Regal Blue	K01901A07	Semi-Flat Black	K01613A07
True Blue (OSHA Safety Blue)	K01910A07	Gloss Black	K01601A07
Purple	K01913A07	PRIMERS (ALKYD ENAMELS) 16 oz. (12 oz. net wt.)	
Hunter Green	K02001A07	Platinum	K01314A07
Emerald Green	K02016A07	White	K01315A07
Cherry Red	K02101A07	Charcoal Black	K01316A07
Banner Red	K02108A07	Ruddy Brown	K01317A07
Safety Orange (Pumpkin)	K02411A07	Gray	K01318A07
Leather Brown	K02501A07		
Almond	K01506A07		
Khaki	K02504A07		
Pewter Gray	K01606A07		
Stone Gray	K01605A07		
Shadow Gray	K01604A07		
Smoke Gray	K01608A07		
Gloss White	K01501A07		
Flat White	K01502A07		
Semi-Gloss White	K01508A07		



PRODUCT SELECTION GUIDE

PRODUCT	RUST TOUGH®	TOUGH COAT®	ACRYLI-QUIK™
Formula	Acrylic Alkyd Enamel	Acrylic Alkyd Enamel	Acrylic Lacquer Enamel
VOC/MIR Compliant	Yes	Yes	Yes
Hiding	Best	Very Good	Good
Durability	Best	Very Good	Good
Dry to the Touch	25 minutes	15 minutes	8 minutes
Recoat Window	Before 2 hours or after 48 hours	Before 2 hours or after 48 hours	Anytime (not for use over acrylics)
Cleanup	Mineral spirits, turpentine (wet). When dry, lacquer thinner, stripper.	Mineral spirits, turpentine (wet). When dry, lacquer thinner, stripper.	Lacquer thinner
Corrosion Resistance	Excellent with or without primer.	Good by itself. Very good with primer.	Excellent with primer.
Gloss	High	High	High
Gasoline & Oil Resistance	Film does not soften.	Film softens after 15 minutes.	Film softens after 15 minutes.