



FOOD GRADE SYNTHETIC GREASE

Pure synthetic multi-service, non-melting, waterproof grease fortified with P.T.F.E. Designed specifically to lubricate, seal out water, and resist chemical attack under the most demanding conditions. With its excellent film strength and extreme pressure qualities, forms a tough, durable film of lubrication that prevents metal-to-metal contact.

APPLICATION & PERFORMANCE

- Non-melting and waterproof
- Extreme pressure performance
- Resists corrosion and chemical attack

LU207

CONTAINS P.T.F.E.

SKU	SIZE
S00207000	14.25 oz/403 g Aerosol



FOOD GRADE SYNTHETIC OIL

Waterproof, synthetic lubricating fluid that does not emulsify with water and has excellent extreme pressure characteristics. Approved for use in food processing, water and wastewater treatment plants where you need excellent anti-wear and anti-rust properties.

APPLICATION & PERFORMANCE

- Does not emulsify with water
- Extreme-pressure performance
- Resists corrosion and chemical attack

LU209

CONTAINS P.T.F.E.

SKU	SIZE
S00209000	14.25 oz/403 g Aerosol



CUTTING OIL

Specifically formulated for all ferrous and nonferrous machining operations. Extends tool life, reducing tool sharpening and downtime. Recommended for all metals, including stainless steel and soft metals such as aluminum, brass and copper. Utilizes a unique combination of friction reducing triglycerides, which aids in a high degree of fluid film protection.

APPLICATION & PERFORMANCE

- Drilling, cutting, threading, sawing, reaming, broaching, grinding
- Works on ferrous and soft metals
- Clings to surfaces
- Reduces friction and wear

LU208

CONTAINS P.T.F.E.

SKU	SIZE
SC0208000	12 oz/340 g Aerosol *
SC0208LQ0	14 fl oz/414 mL Liqui-Sol™ Non-Aerosol Trigger Spray *
S20805000	5 gal/18.9 L Bulk *



FOOD GRADE HIGH TEMP LUBRICANT

Treated with the most effective anti-oxidants, extreme-pressure, anti-wear, and corrosion-protecting additives. P.T.F.E. is added to further enhance load capacity and reduce friction. Excellent extreme pressure lubricity, water resistance and high temperature (12°F to 635°F) performance on chains and much more. Foaming action allows for pinpoint application and penetration.

APPLICATION & PERFORMANCE

- High-temperature performance
- Fortified with extreme-pressure and anti-wear additives
- Foaming action for excellent cling penetration

LU213

CONTAINS P.T.F.E.

SKU	SIZE
S00213000	15 oz /425 g Spray Anyway™ Aerosol