

LONG-TERM METAL PROTECTANTS PERFORMANCE

DESCRIPTION	TYPE OF FILM	INDOOR / OUTDOOR	CORROSION PROTECTION	LONGEVITY	FLASH POINT	DIELECTRIC STRENGTH	NSF REGISTRATION	TEMPERATURE RANGE	BULK
LU710 Waxy Film Protectant	Waxy	Both	Moderate	24 mths	-20°F	2,000	N/A	-20–300°F	✘
LU737 Synthetic Dry Protectant	Dry	Indoor	Light	6–12 mths	145°F	55,600	H2	-20–355°F	✔
LU767 Indoor Metal Protectant	Ultra Thin	Indoor	Moderate	12–15 mths	188°F	48,200	H2	-20–302°F	✔
LU777 Outdoor Metal Protectant	Waxy	Both	Heavy	24 mths	121°F	30,600	H2	-20–300°F	✔



WAXY FILM PROTECTANT

High solids, corrosion preventative compound suitable for a wide range of applications. Provides long term protection of all metal surfaces, including crevice locations. Pliable, firm coating has a polar attraction to metal surfaces and does not crack, age or harden. Dried coating is not flammable and protects electrical connections and wiring. Not harmful to paints and prevents galvanic corrosion. Guards against fretting corrosion. Heavy duty, water displacing film allows greater protection for machinery or parts stored outdoors, especially in salt water or a high humidity atmosphere. Easily removed with petroleum solvents, kerosene or perchloroethylene.

APPLICATION & PERFORMANCE

Chemical plant valves, farm machinery, industrial machinery/equipment, electrical/electronic equipment, steel mills, cable cars, conveyor belts, motorcycles, lugnuts, anywhere wire rope is used.

LU710

120-29

145

24

1000

SKU	SIZE
SC0710000	12 oz/340 g Aerosol ✘



SYNTHETIC DRY PROTECTANT

A transparent non-staining dry film that cleans, penetrates, lubricates and displaces moisture. Formulated with synthetic additives to assure maximum penetration and protection against rust and corrosion. Resists dust, dirt and oil. Non-staining, waterproof, chemical resistant, and non-conductive. An excellent lubricant for bearings and sliding surfaces, as well as moisture displacement in electrical applications.

APPLICATION & PERFORMANCE

Excellent for bearings and sliding surfaces; displaces moisture in electrical applications.

- Penetrating, greaseless lubricant
- Resists dust and dirt buildup
- Non-flammable propellant
- No chlorinated solvents

LU737

120-29

H2

145

6-12

145

SKU	SIZE
SC0737000	11 oz/312 g Aerosol ✘
S73701000	1 gl/3.78 L Bulk ✘
S73705000	5 gl/18.9 L Bulk ✘

LONG-TERM METAL PROTECTANTS