

FOOD GRADE DRY SILICONE

A low-viscosity silicone formula compatible with most surfaces. Ultra-thin film will not attract dust or dirt and will create a barrier to prevent rust and corrosion.

APPLICATION & PERFORMANCE

Plastic fiber gears, extruded parts, wood-to-wood sliding applications, rubber

- Extra-dry formula for surfaces requiring no transfer
- Improves performance of slide surfaces & sorting chutes
- Will not attract dust, dirt or other contaminants

LU211



SKU	SIZE
S00211000	13.25 oz/375 g Aerosol

FOOD GRADE SILICONE LUBRICANT


A 5% low-viscosity silicone formula compatible with most surfaces. Effective from -40°F to 450°F. Repels water and is non-corrosive to metals.

APPLICATION & PERFORMANCE

Plastic fiber gears, extruded parts, wood-to-wood sliding applications, rubber

- Features Big Button Actuator for wide coverage and comfort
- Resists corrosion and chemical attack

LU212



SKU	SIZE
S00212000	13.25 oz/375 g Aerosol Big Button

HEAVY DUTY SILICONE LUBRICANT

Contains a heavy concentration of high-viscosity silicone which will withstand medium loads and pressures. Reduces wear and friction in applications from -40°F to 450°F. Penetrates the surface and provides a continuous non-staining film that repels dust and dirt.

APPLICATION & PERFORMANCE

Slitters, bushings, knives, guides, slides, locks, conveyors, moving parts, dissimilar metals, air tables, rubber items, high wear areas

- Formulated without methylene chloride
- Non-staining
- Works from -40°F to +450°F
- Reduces friction and wear

LU905



SKU	SIZE
SC0905000	12 oz/340 g Aerosol

FOOD GRADE SILICONE LUBRICANT

A low-viscosity silicone lubricant that is colorless, odorless, and tasteless. Effective from -58°F to 575°F. Prevents sticking without transferring to end products. Can be used in proximity to foods where petroleum products and other organics would contaminate.

APPLICATION & PERFORMANCE

Slides, guide rails, knives, slicers, saws, grinders, dough mixers, guards, heat sealing equipment, conveyors, food racks, ovens, bottling machines

- Formulated without methylene chloride
- Works from -58°F to +575°F
- Low viscosity - no buildup

LU910



SKU	SIZE
SC0910000	12 oz/340 g Aerosol