

## ZINC RICH GALVANIZING PERFORMANCE

DESCRIPTION	TYPE	FORMAT	APPEARANCE	% ZINC DRY FILM	TEMPERATURE RANGE
WL740 Zinc Rich Galvanizing Compound	Epoxy	Aerosol (Upright & Inverted) Bulk	Medium Gray	92%	600°F (Max)



# WL740

PREVENTS CORROSION	MAX TEMP 600°F/ 316°C	H 2 F 2 R 1	92% Zn DRY FILM
--------------------	-----------------------------	-------------------	-----------------------

### ZINC-RICH GALVANIZING COMPOUND

A high performance primer containing 97% pure zinc dust pigment blended with epoxy resin. Stops rust by electro-chemical action on steel or galvanized coatings. Self-sacrificing zinc protects the base metal, preserves strength, and prevents rust creepage when the area is penetrated or scratched. Delivers protection against corrosion equal to or better than hot dipped galvanizing.

#### APPLICATION & PERFORMANCE

Automotive, power plants and refineries, industrial tanks, piping, welded joints, bridges, farm equipment, fences, ornamental iron, gutters, structural steel, transmission towers, galvanized surfaces

- 92% Zinc Dry Film
- Stops rust
- Low VOC
- Non sagging formula

SKU	SIZE
SC0740000	14 oz/396 g Aerosol 🇨🇦
SC0740INV	14 oz/396 g Inverted Aerosol 🇨🇦
SC0740Q00	1 qt/946 mL Bulk 🇨🇦
SC0740010	1 gl/3.78 L Bulk 🇨🇦

## AVAILABLE IN BULK!



ZINC RICH GALVANIZING