# SAFETY DATA SHEET

SC0848000

## **Section 1. Identification**

Product name : EL™848 Heavy Duty Flash Free® Electrical Solvent Aerosol

Product code : SC0848000

Other means of : Not available.

identification

Product type : Aerosol.

Relevant identified uses of the substance or mixture and uses advised against

Paint or paint related material.

Manufacturer : Sprayon Products Group

101 W. Prospect Avenue, Cleveland, Ohio 44115

Emergency telephone number of the company

: US / Canada: (800) 424-9300

Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

Product Information Telephone Number

: US / Canada: (800) 247-3266

Mexico: Not Available

Regulatory Information Telephone Number

: US / Canada: (216) 566-2902

Mexico: Not Available

**Transportation Emergency** 

**Telephone Number** 

: US / Canada: (800) 424-9300

Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

## Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: GASES UNDER PRESSURE - Compressed gas SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

GERM CELL MUTAGENICITY - Category 2

CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -

Category 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 2.5%

(oral), 2.5% (dermal), 2.5% (inhalation)

**GHS** label elements

Hazard pictograms







Signal word : Danger

Date of issue/Date of revision : 6/23/2022 Date of previous issue : 3/1/2022 Version : 9 1/14

SC0848000 EL™848 Heavy Duty Flash Free® Electrical Solvent Aerosol

SHW-85-NA-GHS-US

## Section 2. Hazards identification

### **Hazard statements**

: Contains gas under pressure; may explode if heated.

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Suspected of causing genetic defects.

May cause cancer.

May cause damage to organs through prolonged or repeated exposure.

#### **Precautionary statements**

#### **Prevention**

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Wash thoroughly after handling.

#### Response

: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

## **Storage**

: Store locked up. Protect from sunlight. Store in a well-ventilated place. Keep container tightly closed.

## **Disposal**

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

# Supplemental label elements

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.

This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.

Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.

# Hazards not otherwise classified

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

: Not available.

## **CAS** number/other identifiers

| Ingredient name   | % by weight | CAS number |
|-------------------|-------------|------------|
| Trichloroethylene | ≥90 - ≤98   | 79-01-6    |
| Carbon Dioxide    | ≤3          | 124-38-9   |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision: 6/23/2022Date of previous issue: 3/1/2022Version: 92/14SC0848000EL™848 Heavy Duty Flash Free® Electrical Solvent AerosolSHW-85-NA-GHS-US

## Section 4. First aid measures

## **Description of necessary first aid measures**

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

**Inhalation**: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed

person may need to be kept under medical surveillance for 48 hours.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing

before reuse. Clean shoes thoroughly before reuse.

**Ingestion**: Wash out mouth with water. Remove dentures if any. If material has been swallowed

and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious

immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt

person. If unconscious, place in recovery position and get medical attention

or waistband.

### Most important symptoms/effects, acute and delayed

## Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness. May cause respiratory irritation.

**Skin contact**: Causes skin irritation.

Ingestion : Can cause central nervous system (CNS) depression.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain or irritation

watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

**Skin contact**: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Date of issue/Date of revision : 6/23/2022 Date of previous issue : 3/1/2022 Version : 9 3/14

SC0848000 EL™848 Heavy Duty Flash Free® Electrical Solvent Aerosol SHW-85-NA-GHS-US

## Section 4. First aid measures

## Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments
Protection of first-aiders

: No specific treatment.

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

## **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

: In a fire or if heated, a pressure increase will occur and the container may burst. Bursting aerosol containers may be propelled from a fire at high speed.

 Decomposition products may include the following materials: carbon dioxide carbon monoxide

halogenated compounds

carbonyl halides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.

Date of issue/Date of revision : 6/23/2022 Date of previous issue : 3/1/2022 Version : 9 4/14

SC0848000 EL™848 Heavy Duty Flash Free® Electrical Solvent Aerosol

SHW-85-NA-GHS-US

## Section 6. Accidental release measures

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

## Methods and materials for containment and cleaning up

## **Small spill**

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### **Precautions for safe handling**

### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Empty containers retain product residue and can be hazardous.

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits (OSHA United States)

| Ingredient name   | CAS#     | Exposure limits   |
|-------------------|----------|---|
| Trichloroethylene | 79-01-6  | OSHA PEL Z2 (United States, 2/2013).  TWA: 100 ppm 8 hours.  CEIL: 200 ppm  AMP: 300 ppm 5 minutes.  ACGIH TLV (United States, 1/2021).  TWA: 10 ppm 8 hours.  STEL: 25 ppm 15 minutes. |
| Carbon Dioxide    | 124-38-9 | ACGIH TLV (United States, 1/2021). Oxygen Depletion [Asphyxiant]. TWA: 5000 ppm 8 hours.  |

Date of issue/Date of revision: 6/23/2022Date of previous issue: 3/1/2022Version: 95/14SC0848000EL™848 Heavy Duty Flash Free® Electrical Solvent AerosolSHW-85-NA-GHS-US

# Section 8. Exposure controls/personal protection

TWA: 9000 mg/m³ 8 hours.

STEL: 30000 ppm 15 minutes.

STEL: 54000 mg/m³ 15 minutes.

NIOSH REL (United States, 10/2020).

TWA: 5000 ppm 10 hours.

TWA: 9000 mg/m³ 10 hours.

STEL: 30000 ppm 15 minutes.

STEL: 54000 mg/m³ 15 minutes.

OSHA PEL (United States, 5/2018).

TWA: 5000 ppm 8 hours.

TWA: 9000 mg/m³ 8 hours.

## Occupational exposure limits (Canada)

| Ingredient name   | CAS#    | Exposure limits  |  |
|-------------------|---------|--|--|
| Trichloroethylene | 79-01-6 | CA Alberta Provincial (Canada, 6/2018).  15 min OEL: 537 mg/m³ 15 minutes.  15 min OEL: 100 ppm 15 minutes.  8 hrs OEL: 50 ppm 8 hours.  8 hrs OEL: 269 mg/m³ 8 hours.  CA British Columbia Provincial (Canada, 6/2021).  TWA: 10 ppm 8 hours.  STEL: 25 ppm 15 minutes.  CA Ontario Provincial (Canada, 6/2019).  TWA: 10 ppm 8 hours.  STEL: 25 ppm 15 minutes.  CA Quebec Provincial (Canada, 6/2021).  TWAEV: 50 ppm 8 hours.  TWAEV: 269 mg/m³ 8 hours.  STEV: 200 ppm 15 minutes.  STEV: 1070 mg/m³ 15 minutes.  CA Saskatchewan Provincial (Canada, 7/2013).  STEL: 100 ppm 15 minutes.  TWA: 50 ppm 8 hours. |  |

## Occupational exposure limits (Mexico)

|                   | CAS#    | Exposure limits   |
|-------------------|---------|---|
| Trichloroethylene | 79-01-6 | NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 10 ppm 8 hours. STEL: 25 ppm 15 minutes. |

# Appropriate engineering controls

controls

**Environmental exposure** 

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- : This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **Individual protection measures**

 Date of issue/Date of revision
 : 6/23/2022
 Date of previous issue
 : 3/1/2022
 Version
 : 9
 6/14

 SC0848000
 EL™848 Heavy Duty Flash Free® Electrical Solvent Aerosol
 SHW-85-NA-GHS-US

## Section 8. Exposure controls/personal protection

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk

assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

**Skin protection** 

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be

> worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the

protection time of the gloves cannot be accurately estimated.

**Body protection** : Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before

handling this product.

: Appropriate footwear and any additional skin protection measures should be selected Other skin protection

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

**Respiratory protection** Based on the hazard and potential for exposure, select a respirator that meets the

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

## **Appearance**

**Physical state** : Liquid.

Color : Not available. Not available. Odor Not available. **Odor threshold** Ha : Not applicable. **Melting point/freezing point** : Not available. **Boiling point, initial boiling** : Not available.

point, and boiling range

Flash point : Closed cup: Not applicable.

**Evaporation rate** : 5 (butyl acetate = 1)

**Flammability** : Not available. Lower and upper explosion : Lower: 12.5% limit/flammability limit Upper: 90%

: 101.3 kPa (760 mm Hg) Vapor pressure

Relative vapor density : 4.53 [Air = 1]

1.44 Relative density

**Solubility** : Not available. Partition coefficient: n-: Not applicable.

octanol/water

Date of issue/Date of revision 7/14 : 6/23/2022 Date of previous issue : 3/1/2022 Version: 9

SC0848000 EL™848 Heavy Duty Flash Free® Electrical Solvent Aerosol SHW-85-NA-GHS-US

# Section 9. Physical and chemical properties

**Auto-ignition temperature** : Not available. **Decomposition temperature** : Not available.

**Viscosity** Kinematic (40°C (104°F)): <20.5 mm<sup>2</sup>/s (<20.5 cSt)

**Molecular weight** Not applicable.

**Aerosol product** 

Type of aerosol : Spray Heat of combustion : 0 kJ/g

# Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

**Possibility of hazardous** 

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

**Incompatible materials** : No specific data.

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

# Section 11. Toxicological information

## Information on toxicological effects

## **Acute toxicity**

| Product/ingredient name | Result  | Species | Dose                                   | Exposure          |
|-------------------------|---|---------|--|-------------------|
| Trichloroethylene       | LC50 Inhalation Vapor<br>LD50 Dermal<br>LD50 Oral | Rabbit  | 140700 mg/m³<br>>20 g/kg<br>4920 mg/kg | 1 hours<br>-<br>- |

## Irritation/Corrosion

| Product/ingredient name | Result                   | Species | Score | Exposure               | Observation |
|-------------------------|--------------------------|---------|-------|------------------------|-------------|
| Trichloroethylene       | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 20            | -           |
|                         | Skin - Severe irritant   | Rabbit  | -     | mg<br>24 hours 2<br>mg | -           |

### **Sensitization**

Not available.

## Mutagenicity

Not available.

## Carcinogenicity

Not available.

## **Classification**

| Product/ingredient name | OSHA | IARC | NTP                             |
|-------------------------|------|------|---------------------------------|
| Trichloroethylene       | -    | 1    | Known to be a human carcinogen. |

Date of issue/Date of revision : 6/23/2022 Date of previous issue : 3/1/2022 Version: 9 8/14 SHW-85-NA-GHS-US

# Section 11. Toxicological information

## Reproductive toxicity

Not available.

## **Teratogenicity**

Not available.

## Specific target organ toxicity (single exposure)

| Name              |            | Route of exposure | Target organs                |
|-------------------|------------|-------------------|------------------------------|
| Trichloroethylene | Category 3 |                   | Respiratory tract irritation |
|                   | Category 3 |                   | Narcotic effects             |

## Specific target organ toxicity (repeated exposure)

| Name              | Category   | Route of exposure | Target organs |
|-------------------|------------|-------------------|---------------|
| Trichloroethylene | Category 2 | -                 | -             |

## **Aspiration hazard**

Not available.

Information on the likely

routes of exposure

: Not available.

## Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness. May cause respiratory irritation.

**Skin contact** : Causes skin irritation.

**Ingestion** : Can cause central nervous system (CNS) depression.

## Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : Adverse symptoms r

: Adverse symptoms may include the following: respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

## Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Date of issue/Date of revision : 6/23/2022 Date of previous issue : 3/1/2022 Version : 9 9/14

SC0848000 EL™848 Heavy Duty Flash Free® Electrical Solvent Aerosol SHW-85-NA-GHS-US

# Section 11. Toxicological information

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

**General**: May cause damage to organs through prolonged or repeated exposure.

**Carcinogenicity**: May cause cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity**: Suspected of causing genetic defects.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

## **Numerical measures of toxicity**

## **Acute toxicity estimates**

| Route | ATE value     |
|-------|---------------|
| Oral  | 5046.15 mg/kg |

# **Section 12. Ecological information**

## **Toxicity**

| Product/ingredient name | Result  | Species  | Exposure           |
|-------------------------|---|--|--------------------|
| Trichloroethylene       | Acute EC50 95000 μg/l Marine water                                    | Algae - Skeletonema costatum   | 96 hours           |
|                         | Acute EC50 36.5 mg/l Fresh water                                      | Algae - Chlamydomonas reinhardtii - Exponential growth phase                 | 72 hours           |
|                         | Acute LC50 20 mg/l Marine water                                       | Crustaceans - Elminius modestus  | 48 hours           |
|                         | Acute LC50 18000 μg/l Fresh water                                     | Daphnia - Daphnia magna  | 48 hours           |
|                         | Acute LC50 3100 µg/l Fresh water                                      | Fish - Jordanella floridae -<br>Juvenile (Fledgling, Hatchling,<br>Weanling) | 96 hours           |
|                         | Chronic EC10 12.3 mg/l Fresh water                                    | Algae - Chlamydomonas reinhardtii - Exponential growth phase                 | 72 hours           |
|                         | Chronic NOEC 2.3 mg/l Fresh water Chronic NOEC 10568 mg/l Fresh water | Daphnia - Daphnia magna<br>Fish - Jordanella floridae - Fry                  | 21 days<br>28 days |

## Persistence and degradability

Not available.

## **Bioaccumulative potential**

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| Trichloroethylene       | -      | 17  | low       |

## **Mobility in soil**

 Date of issue/Date of revision
 : 6/23/2022
 Date of previous issue
 : 3/1/2022
 Version
 : 9
 10/14

 SC0848000
 EL™848 Heavy Duty Flash Free® Electrical Solvent Aerosol
 SHW-85-NA-GHS-US

# Section 12. Ecological information

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

## **Disposal methods**

: This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

# **Section 14. Transport information**

|                            | DOT<br>Classification | TDG<br>Classification | Mexico<br>Classification | IATA  | IMDG     |
|----------------------------|-----------------------|-----------------------|--------------------------|---|----------|
| UN number                  | UN1950                | UN1950                | UN1950                   | UN1950  | UN1950   |
| UN proper shipping name    | AEROSOLS              | AEROSOLS              | AEROSOLS                 | AEROSOLS,<br>NON-<br>FLAMMABLE,<br>TOXIC,<br>CONTAINING<br>SUBSTANCES<br>IN DIVISION 6.1,<br>PACKING<br>GROUP III | AEROSOLS |
| Transport hazard class(es) | 2.2                   | 2.2                   | 2.2                      | 2.2 (6.1)   | 2.2      |
| Packing group              | •                     | -                     | -                        | -   | -        |
| Environmental hazards      | No.                   | No.                   | No.                      | No.   | No.      |
|                            |                       |                       |                          |   |          |

Date of issue/Date of revision

: 6/23/2022

Date of previous issue

: 3/1/2022

Version :9

11/14

SC0848000 EL™848 Heavy Duty Flash Free® Electrical Solvent Aerosol

SHW-85-NA-GHS-US

#### Section 14. Transport information Additional Product classified information as per the following sections of the Transportation of **Dangerous Goods** Regulations: 2.13-2.17 (Class 2). Dependent upon Dependent upon Dependent upon Dependent upon Dependent upon container size, this product may ship under the Limited Quantity shipping exception. shipping exception. shipping exception. shipping exception. shipping exception.

Special precautions for user :

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according: Not available. to IMO instruments

Proper shipping name

: Not available.

# Section 15. Regulatory information

U.S. Federal regulations

: TSCA 5(a)2 final significant new use rules: Trichloroethylene

List name **Chemical name Notes** 

United States - TSCA 5(a) Trichloroethylene

2 - Final significant new

use rules

This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.

#### **SARA 313**

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

#### California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

## **International regulations**

International lists

: Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

Taiwan Chemical Substances Inventory (TCSI): Not determined.


**Thailand inventory**: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

Date of issue/Date of revision : 6/23/2022 Date of previous issue : 3/1/2022 Version: 9 12/14

SC0848000 EL™848 Heavy Duty Flash Free® Electrical Solvent Aerosol

## Section 16. Other information

## **Hazardous Material Information System (U.S.A.)**



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

### Procedure used to derive the classification

| Classification  | Justification      |
|---|--------------------|
| GASES UNDER PRESSURE - Compressed gas                                 | Calculation method |
| SKIN CORROSION/IRRITATION - Category 2                                | Calculation method |
| SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A                      | Calculation method |
| GERM CELL MUTAGENICITY - Category 2                                   | Calculation method |
| CARCINOGENICITY - Category 1A   | Calculation method |
| SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract   | Calculation method |
| irritation) - Category 3  |                    |
| SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - | Calculation method |
| Category 3  |                    |
| SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2       | Calculation method |

### **History**

**Date of printing** 6/23/2022 Date of issue/Date of 6/23/2022

revision

**Date of previous issue** 3/1/2022

**Version** 9

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group **UN = United Nations** 

Indicates information that has changed from previously issued version.

## **Notice to reader**

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer,

Date of issue/Date of revision 13/14 : 6/23/2022 Date of previous issue : 3/1/2022 Version: 9 SHW-85-NA-GHS-US

## Section 16. Other information

or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Date of issue/Date of revision : 6/23/2022 Date of previous issue : 3/1/2022 Version : 9 14/14