

PP 810

Shurtape®
TRUE TO YOUR WORK™

PREMIUM GRADE SOLVENT-BASED ACRYLIC PACKAGING TAPE

TYPICAL APPLICATIONS

- For sealing light- to medium-weight cartons in everyday shipping and handling environments
- Also used for bundling and securing loose objects
- Can also be used to repair corrugated cartons, paper and film containers
- Use with a hand-held dispenser

PRODUCT FEATURES

- Excellent adhesion and holding power to protect contents from pilferage
- Seals out moisture and dirt
- Performs in a range of temperatures

CONSTRUCTION

Overall Grade/Function: Premium
Backing: 25 micron biaxially oriented polypropylene cast film
Adhesive: Solvent-based acrylic

STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

50 m 100 m

Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

CID A-A-1684C

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



CLEAR
(CLR)



TAN
(TAN)

PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	22 lbs/in width	38.5 N/10 mm
Adhesion to Stainless Steel	22 oz/in width	2.41 N/10 mm
Adhesion to Backing	16 oz/in width	1.75 N/10 mm
Adhesion to Kraft	10 oz/in width	1.09 N/10 mm
Thickness	1.8 mils	0.046 mm
Elongation	140%	140%
Application Temperature Range	20 F to 110 F	-7 C to 43 C
Service Temperature Range	-20 F to 180 F	-29 C to 82 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

