

ON-GRADE ADJUSTABLE FLOOR DRAIN

» 842 SERIES

SPECIFICATION

Sioux Chief 842 Series adjustable floor drain shall be used where necessary in drainage systems. Floor drain shall have an MIP thread connection for use with FIP thread adapters/fittings. Designed in accordance with ASME A112.6.3.

MATERIALS

Ring/strainer: Nickel-bronze

Thread body: cast iron

STRAINER LOAD RATING

Nickel-bronze: 1,000 lbs (Light duty, heel-proof)

STRAINER FREE-AREA

	2" Drain	3" Drain	4" Drain
Round NikBrz:	4.5 in ²	8.5 in ²	13.4 in ²
Square NikBrz:	7.6 in ²	12.75 in ²	16.4 in ²


DIMENSIONS

	2" Drain	3" Drain	4" Drain
A. Connection	2" MIP	3" MIP	4" MIP
B. Ring/strainer diameter			
Round	4½"	5½"	6½"
Square	6½"	5⅞"	7"
C. Overall height	2⅞"	3"	3"

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



842-3iLNQ



Create Item Number

842-ABC

e.g. **842-3iLNRVH:** Floor drain with 3" MIP connection, round nickel-bronze hinged strainer with vandal-resistant screws

CONNECTION A

2iL = 2" MIP

3iL = 3" MIP

4iL = 4" MIP

RING & STRAINER B

NR = Round nickel-bronze

NQ = Square nickel-bronze

OPTIONS (FACTORY INSTALLED) C

V = Vandal-resistant cover screws

H = Hinged strainer¹

E = Extended ring²

¹Available for 842-36L_R/Q and 842-4L_R/Q models only

²Available for 842-36LNR and 842-4LNR models only