

Sillcock

Standard

- Larger 2¼" diameter mounting flange with easy to use pilot holes



117-22

Item No	Description	Pkg	Min Qty	Case Qty
STANDARD SILLCOCK				
117-22	½" FSWT sillcock	B	10	100

Frost-Proof† Anti-Siphon Sillcock

Standard Valve

- Longer stem keeps knuckles from scraping on hose threads
- Thicker, easier turning handle
- Nickel-plated brass body with black metal handle
- Spout aligning lug
- Female sweat model has 6" of full-slip and compression connection includes 3" of full-slip



118-210

¼-Turn

- Extended tailpiece for ease of installation
- Extra-large mounting flange
- Spout alignment feature
- Nickel-plated brass body
- ANSI/NSF 61 listed



118-210PK



119-210CPK

Item No	Connection	Length	Pkg	Min Qty	Case Qty
STANDARD					
118-204	½" MIP × ½" FSWT	4"	B	2	40
118-206	½" MIP × ½" FSWT	6"	B	2	40
118-208	½" MIP × ½" FSWT	8"	B	2	40
118-210	½" MIP × ½" FSWT	10"	B	2	40
118-210PK	½" FSWT, full-slip	10"	C*	5	5
118-212	½" MIP × ½" FSWT	12"	B	2	40
¼-TURN					
119-204	½" MIP × ½" FSWT	4"	B	1	25
119-206	½" MIP × ½" FSWT	6"	B	1	25
119-208	½" MIP × ½" FSWT	8"	B	1	25
119-210	½" MIP × ½" FSWT	10"	B	1	25
119-210PK	½" FSWT, full-slip	10"	C*	5	5
119-212	½" MIP × ½" FSWT	12"	B	1	25
119-210CPK	⅝" O.D. compression	10"	C*	5	5

† As with all frost-proof hydrants, removal of hose is required to insure against freezing and breaking.

