Replace-A-Valve[™]

Full-Port Ball Valve

Sweat or Compression Connection

- 1/2" and 3/4" full-slip tailpieces for easy installation
- Sweat or compression models
- Full-port ball valves



600-204V



Easy full-slip installation. Perfect for replacing leaking or corroded valves, or valves that have seized up.



Item No	Connection	Length	NO LEAD	Pkg	Min Qty	Case Qty					
SWEAT											
600-204V	½" CTS × ½" CTS, clamshell	61/4"		C*	10	10					
600-304V	3/4" CTS × 3/4" CTS, clamshell	7"		C*	10	10					
	COMPRESSION										
600-204CV	½" CTS × ½" CTS, clamshell	93/8"		C*	10	10					
600-304CV	3/4" CTS × 3/4" CTS, clamshell	101/2",		C*	10	10					
LEAD-FREE SWEAT											
600-G204V	½" CTS × ½" CTS, individually boxed	61/4"	1	C*	10	10					
600-G304V	3/4" CTS × 3/4" CTS, individually boxed	10½"	1	C*	10	10					
	LEAD-FREE COMPRESSI	ON									
600-G204CV	½" CTS × ½" CTS, clamshell	93/8"	1	C*	10	10					
600-G304CV	3/4" CTS × 3/4" CTS, clamshell	10½"	/	C*	10	10					

Water Heater Connector

FIP × Female Sweat Elbow

- Brass full-port ball valve available
- Brass FIP swivel nut includes gasket
- For use on shower risers and tub spouts, non-pressure fitting applications



Item No	Connection	Dimer	Dimensions		NO	Pkg	Min	Case
		A	В	Valve	LEAD	1 1/6	Qty	Qty
631-G305FP	3/4" FIP swivel × 3/4" FSWT	3"	5"	1	/	В	25	25
631-33F	3/4" FIP swivel × 3/4" FSWT	3"	3"		✓	В	25	25

