


Fat Max™

Large-Capacity Floor Drain

- ABS or PVC solvent weld connection
- Low profile design with anchor flange for a solid installation



860-3PZ



PVC Item No	ABS Item No	Dimensions				Pkg	Min Qty	Case Qty
		A	B	C	D			
WITH ABS OR PVC STRAINER								
860-2P	860-2A	2"	9"	8½"	6⅜"	B*	1	4
860-3P	860-3A	3 × 4"	9"	8½"	6⅜"	B*	1	4
860-4P	860-4A	4"	9"	8½"	6⅜"	B*	1	4
860-6P	860-6A	6"	9"	8½"	8⅛"	B*	1	1
WITH NICKEL BRONZE RING & STRAINER								
860-2PN	860-2AN	2"	9¾"	9⅝"	7⅝"	B*	1	4
860-3PN	860-3AN	3 × 4"	9¾"	9⅝"	7⅝"	B*	1	4
860-4PN	860-4AN	4"	9¾"	9⅝"	7⅝"	B*	1	4
860-6PN	860-6AN	6"	9¾"	9⅝"	8⅝"	B*	1	1
WITH STAINLESS STEEL RING & STRAINER								
860-2PZ	860-2AZ	2"	9¾"	9⅝"	7⅝"	B*	1	4
860-3PZ	860-3AZ	3 × 4"	9¾"	9⅝"	7⅝"	B*	1	4
860-4PZ	860-4AZ	4"	9¾"	9⅝"	7⅝"	B*	1	4
860-6PZ	860-6AZ	6"	9¾"	9⅝"	8⅝"	B*	1	1
WITH CAST IRON RING & STRAINER								
860-2Pi	860-2Ai	2"	9⅝"	8½"	6⅜"	B*	1	2
860-3Pi	860-3Ai	3 × 4"	9⅝"	8½"	6⅜"	B*	1	2
860-4Pi	860-4Ai	4"	9⅝"	8½"	6⅜"	B*	1	2
860-6Pi	860-6Ai	6"	9⅝"	8½"	8⅛"	B*	1	2

SUPPLY

DRAINAGE

SUPPORT

APPENDIX


Fat Max™

Large-Capacity Floor Drain

- Cast iron no-hub or push-joint connection
- Low profile design with anchor flange for a solid installation



860-23i



No-Hub Item No	Push-Joint Item No	Dimensions				Pkg	Min Qty	Case Qty
		A	B	C	D†			
WITH NICKEL BRONZE RING & STRAINER								
860-22N	860-62N	2"	9¾"	9⅝"	7¼"	B*	1	1
860-23N	860-63N	3"	9¾"	9⅝"	7¼"	B*	1	1
860-24N	860-64N	4"	9¾"	9⅝"	7¼"	B*	1	1
860-26N	—	6"	9¾"	9⅝"	7¼"	B*	1	1
WITH STAINLESS STEEL RING & STRAINER								
860-22Z	860-62Z	2"	9¾"	9⅝"	7¼"	B*	1	1
860-23Z	860-63Z	3"	9¾"	9⅝"	7¼"	B*	1	1
860-24Z	860-64Z	4"	9¾"	9⅝"	7¼"	B*	1	1
860-26Z	—	6"	9¾"	9⅝"	7¼"	B*	1	1
WITH CAST IRON STRAINER								
860-22i	860-62i	2"	9"	8½"	6¾"	B*	1	1
860-23i	860-63i	3"	9"	8½"	6¾"	B*	1	1
860-24i	860-64i	4"	9"	8½"	6¾"	B*	1	1
860-26i	—	6"	9"	8½"	7¼"	B*	1	1

† Add ⅜" to this dimension for push-joint connection