

## T-Cone™

### Expandable Pipe Plug

- Easy to install and remove
- Tighten with a crescent wrench
- No metal parts to rust



882-ST302

Item No	Description	Plug Gasket O.D.	Pkg	Min Qty	Case Qty
<b>SCH. 40 PIPE BARREL PLUG</b>					
882-ST152	1½" raised-head pipe plug	1.61"	B	10	100
882-ST202	2" raised-head pipe plug	2.067"	B	10	100
882-CS202	2" flush-head pipe plug	2.067"	B	10	100
882-ST302	3" raised-head pipe plug	3.068"	B	10	100
882-CS302	3" flush-head pipe plug	3.068"	B	10	100
882-ST402	4" raised-head pipe plug	4.026"	B	10	100
882-CS402	4" flush-head pipe plug	4.026"	B	10	100
882-ST602	6" raised-head pipe plug	6.065"	B	10	10
882-ST802	8" raised-head pipe plug	7.981"	B	10	10
<b>SCH. 40 HUB PLUG</b>					
882-ST300	3" raised-head socket plug	3.50"	B	10	100
<b>FIP CLEANOUT PLUG</b>					
882-EB152	1½" raised-head cleanout plug	1.78"	B	10	100
882-EB220	2" raised-head cleanout plug	2.255"	B	10	100
882-EB320	3" raised-head cleanout plug	3.378"	B	10	100
882-EB350	3½" raised-head cleanout plug	3.85"	B	10	100
882-EB420	4" raised-head cleanout plug	4.336"	B	10	100

## Hand Tite™

### Mechanical Test Plug

- For 4" – 6" models, use ¾" male garden hose thread adapter and drill-out wall on stem for water or air by-pass tests
- For 8" model, tap stem ½" NPT and drill through bulk head to allow for water or air by-pass tests
- Nylon body and ASTM 361 rubber gasket



882-96

Item No	Description	Pkg	Min Qty	Case Qty
882-95	5" large diameter test plug	B	1	30
882-96	6" large diameter test plug	B	1	30
882-98	8" large diameter test plug	B	1	12

