

Hangs Tuff™

DWV Pipe Hanger

Patent # 5,385,320

- Strong and rigid I-beam design keeps pipe secure
- Two ring-shank nails conveniently supplied
- 100% corrosion proof, impact resistant ABS
- Can be glued to ABS or PVC pipe with all-purpose glue



Two nails supplied for easy installation.



Opposing holes are 1/2" on center.




Cradles pipe before final installation.



Locking finger holds pipe in place.



Locking finger allows installation at all angles.



Extend length by using all thread rod and vinyl-coated clamps or L-bracket.



SUPPLY

DRAINAGE

SUPPORT

APPENDIX




Related Products
Vinyl-Coated Clamp

p 434

| Item No. | Description | Dimension | | Pkg | Min Qty | Case Qty |
|------------------|---------------------------------|-----------------------------------|------|-----|---------|----------|
| | | A | B | | | |
| WHITE | | | | | | |
| 553-6W | 1½" Sch. 40 | 8 ⁵ / ₈ " | 10" | C* | 50 | 50 |
| 553-6WPK3 | 1½" Sch. 40, 10/bag | 8 ⁵ / ₈ " | 10" | C* | 1 | 5 |
| 553-7W | 2" Sch. 40 | 8 ¹⁵ / ₁₆ " | 10½" | C* | 50 | 50 |
| 553-7WPK3 | 2" Sch. 40, 10/bag | 8 ¹⁵ / ₁₆ " | 10½" | C* | 1 | 5 |
| 553-8W | 3" Sch. 40 | 9 ⁷ / ₁₆ " | 11¾" | C* | 50 | 50 |
| 553-8WPK3 | 3" Sch. 40, 10/bag | 9 ⁷ / ₁₆ " | 11¾" | C* | 1 | 5 |
| 553-830W | 3" Sch. 30 | 9 ⁵ / ₁₆ " | 11¾" | C* | 50 | 50 |
| 553-830WPK3 | 3" Sch. 30, 10/bag | 9 ⁵ / ₁₆ " | 11¾" | C* | 1 | 5 |
| 553-9W | 4" Sch. 40 | 9 ¹⁵ / ₁₆ " | 12¾" | C* | 25 | 25 |
| 553-9WPK3 | 4" Sch. 40, 10/bag | 9 ¹⁵ / ₁₆ " | 12¾" | C* | 1 | 5 |
| BLACK | | | | | | |
| 553-6 | 1½" Sch. 40 | 8 ⁵ / ₈ " | 10" | C* | 50 | 50 |
| 553-6PK3 | 1½" Sch. 40, 10/bag | 8 ⁵ / ₈ " | 10" | C* | 1 | 5 |
| 553-7 | 2" Sch. 40 | 8 ¹⁵ / ₁₆ " | 10½" | C* | 50 | 50 |
| 553-7PK3 | 2" Sch. 40, 10/bag | 8 ¹⁵ / ₁₆ " | 10½" | C* | 1 | 5 |
| 553-8 | 3" Sch. 40 | 9 ⁷ / ₁₆ " | 11¾" | C* | 50 | 50 |
| 553-8PK3 | 3" Sch. 40, 10/bag | 9 ⁷ / ₁₆ " | 11¾" | C* | 1 | 5 |
| 553-9 | 4" Sch. 40 | 9 ¹⁵ / ₁₆ " | 12¾" | C* | 25 | 25 |
| 553-9PK3 | 4" Sch. 40, 10/bag | 9 ¹⁵ / ₁₆ " | 12¾" | C* | 1 | 5 |
| L-BRACKET | | | | | | |
| 521-210 | L-bracket for ¾" all thread rod | | | B | 25 | 100 |

According to all national codes, ABS or PVC DWV pipe is to be supported every four feet or less. When hanging steel or cast iron pipe, install Hangs Tuff™ two feet on center (or less), cinch with cable tie, and anchor with min 1½", #10 wood screws.



Except 553-830W