

## PRECISION 90 PEAR HEAD RATCHET REPAIR KITS

Product #	Drive Size (in)	Ratchets
<b>J47HTCFRK</b>	1/4	J4749HTC, J4749HTCBL, J4750HTC, J4750HTCF
<b>J52HTCFRK</b>	3/8	J5249HTC, J5249HTCBL, J5250HTC, J5250HTCBL, J5249HTCF, J5250HTCF
<b>J54HTCFRK</b>	1/2	J5449HTC, J5449HTCBL, J5450HTC, J5450HTCBL, J5426HTC, J5426HTCBL, J5450HTCF



## PREMIUM PEAR HEAD RATCHETS

- ▶ Small pear head design for access in tight, hard-to-reach work areas.
- ▶ 45-tooth gear provides balance between 8° articulation angle and high torque carrying capacity.
- ▶ Patented, sealed-head design helps prevent debris from entering ratchet mechanism reducing wear. Also, helps to keep lubrication contained within the components.
- ▶ Low profile reversing lever design for quick, one-hand operation.
- ▶ Contoured, ergonomically designed handle for comfort. Knurled bands allow for increased grip and slip resistance.
- ▶ Full polish finishes offer double nickel chrome plating for enhanced corrosion protection.
- ▶ Field repairable.



Product #	Drive Size (in)	Finish	Style	Overall Length (in)	Weight (lbs)	Repair Kit Part #
<b>J4749XL*</b>	1/4	Full Polish	Pear Head	5-5/8	0.25	J4749XLRK
<b>J4749XLBL*</b>	1/4	Black Oxide	Pear Head	5-9/16	0.25	J4749XLRK
<b>J4749XLQR*</b>	1/4	Full Polish	Quick-Release	5-5/8	0.25	J4749XLQRRK
<b>J4749XLQRBL*</b>	1/4	Black Oxide	Quick-Release	5-5/8	0.25	J4749XLQRRK
<b>J5249XL*</b>	3/8	Full Polish	Pear Head	8-1/2	0.86	J5249XLRK
<b>J5249XLBL*</b>	3/8	Black Oxide	Pear Head	8-1/2	0.87	J5249XLRK
<b>J5249XLQR*</b>	3/8	Full Polish	Quick-Release	8-1/2	0.86	J5249XLQRRK
<b>J5249XLQRBL*</b>	3/8	Black Oxide	Quick-Release	8-1/2	0.86	J5249XLQRRK
<b>J5449XL</b>	1/2	Full Polish	Pear Head	10-1/2	1.72	J5449XLRK
<b>J5449XLBL</b>	1/2	Black Oxide	Pear Head	10-1/2	1.72	J5449XLRK
<b>J5449XLQR</b>	1/2	Full Polish	Quick-Release	10-1/2	1.72	J5449XLQRRK
<b>J5449XLQRBL</b>	1/2	Black Oxide	Quick-Release	10-1/2	1.72	J5449XLQRRK

\*SAE AS4283C ASME B107.110-2012

## LONG HANDLE



Product #	Drive Size (in)	Finish	Style	Overall Length (in)	Weight (lbs)	Repair Kit Part #
<b>J5250XL*</b>	3/8	Full Polish	Pear Head	11	1.03	J5249XLRK
<b>J5250XLBL*</b>	3/8	Black Oxide	Pear Head	11	0.98	J5249XLRK
<b>J5250XLQRBL*</b>	3/8	Black Oxide	Quick-Release	11	1.03	J5249XLQRRK
<b>J5450XL</b>	1/2	Full Polish	Pear Head	15	2.18	J5449XLRK
<b>J5450XLQR</b>	1/2	Full Polish	Quick-Release	15	2.18	J5449XLQRRK
<b>J5450XLBL</b>	1/2	Black Oxide	Pear Head	15	2.18	J5449XLRK
<b>J5450XLQRBL</b>	1/2	Black Oxide	Quick-Release	15	2.18	J5449XLQRRK

\*SAE AS4283C ASME B107.110-2012