FACOM® INSULATED RATCHETS

- > Sockets and accessories secured by spring -ball.
- 2 Color warning handle insulation color changes from orange to yellow if Insulation integrity compromised.
- > For manual use.
- Insulated to 1000V AC or 1500 DC.

		Overall	
Product #	Drive Size (in)	Length (in)	Weight (lbs)
R.151AVSE	1/4	4-7/8	0.28
J.151AVSE	3/8	7	0.53
S.151AVSE	1/2	10-3/8	1.24
	•		





SPUD HANDLE RATCHET

- > Tapered handle for aligning bolt holes.
- Spring loaded pellet in male drive plug.
- Black oxide finish.



Product #	Drive Size (in)	Finish	Style	Length (in)	Weight (lbs)	
J5449-14BL	1/2	Black Oxide	Pear Head	14	2.03	
					10145 0407 500	

ASME B107.500



- > The scaffold ratchet is designed for working with scaffolding and other construction applications.
- Socket retained with through hole and pin for safety.
- ▶ Hammer tip reduces vibration and protects fasteners against distortion.
- > Hole in ratchet handle to be used with tether strap.



			Uverali		
Product #	Drive Size (in)	Finish	Style	Length (in)	Weight (lbs)
J5449SC	1/2	Full Polish	Scaffolding	10	2.01
·					

SPINNER RATCHET

- Made from alloy steel.
- Heat-treated for strength and durability.
- ▶ Fits on the drive end of the ratchet for quickly running down the fastener before final tightening with the ratchet.

	Product #	Drive Size (in)	Finish	Overall Length (in)	Weight (lbs)
	J5251	3/8	Full Polish	1-1/2	0.56
-					

ASME B107.110-2012

