



DRIVE ADAPTERS

- Full polish tools meet and exceed stringent aerospace specification AS4984A which requires tools to have a thicker nickel-chrome coating for greater corrosion-resistance.



| Product # | Input Drive (in) | Output Drive (in) | Finish | Overall Length (in) | Weight (lbs) |
|---------------|------------------|-------------------|-------------|---------------------|--------------|
| J5255 | 3/8 | 1/4 | Full Polish | 1 | 0.05 |
| J5256 | 1/4 | 3/8 | Full Polish | 1 | 0.04 |
| J5256B | 1/4 | 3/8 | Black Oxide | 1 | 0.04 |
| J5253 | 3/8 | 1/2 | Full Polish | 1-7/16 | 0.11 |
| J5253B | 3/8 | 1/2 | Black Oxide | 1-7/16 | 0.11 |
| J5254 | 1/2 | 3/8 | Full Polish | 1-3/8 | 0.13 |
| J5653 | 1/2 | 3/4 | Full Polish | 1-11/16 | 0.24 |
| J5653B | 1/2 | 3/4 | Black Oxide | 1-11/16 | 0.24 |
| J5453 | 3/4 | 1/2 | Full Polish | 1-7/8 | 0.39 |
| J5853 | 3/4 | 1 | Full Polish | 2-1/2 | 0.82 |
| J5854 | 1 | 3/4 | Full Polish | 2-7/8 | 1.27 |

ASME B107.110-2012

ADAPTERS & UNIVERSAL JOINTS

LOCKING ADAPTERS

- Includes hex key for easy locking into drive tool.
- Knurl locking ring.

| Product # | Drive Size (in) | Finish | Overall Length (in) | Weight (lbs) |
|--------------------|-----------------|-------------|---------------------|--------------|
| J4759BLS | 1/4 | Black Oxide | 1-11/16 | 0.06 |
| J5260-02BLS | 3/8 | Black Oxide | 2-1/8 | 0.12 |
| J5460-02BLS | 1/2 | Black Oxide | 3 | 0.36 |



UNIVERSAL JOINTS

- Full polish tools meet and exceed stringent aerospace specification AS4984A which requires tools to have a thicker nickel-chrome coating for greater corrosion-resistance.

| Product # | Drive Size (in) | Finish | Overall Length (in) | Weight (lbs) |
|-----------------|-----------------|-------------|---------------------|--------------|
| J4770A | 1/4 | Full Polish | 1-11/32 | 0.04 |
| J4770AB | 1/4 | Black Oxide | 1-11/32 | 0.04 |
| J5270A* | 3/8 | Full Polish | 2 | 0.13 |
| J5270AB* | 3/8 | Black Oxide | 2 | 0.13 |
| J5470A | 1/2 | Full Polish | 2-3/4 | 0.30 |
| J5470AB | 1/2 | Black Oxide | 2-3/4 | 0.30 |
| J5670* | 3/4 | Full Polish | 4 | 1.03 |

*AS4283C ASME B107.110-2012



6 POINT
 8 POINT
 12 POINT
 SPL SPLINE
 HEX
 FULL POLISH
 SATIN
 BLACK OXIDE
 INSULATED