



## 1/4" DRIVE BIT SOCKETS

- Bit holders have a hex opening to hold the bit, allowing the bit holder to take the full load of torque.



J4743



J4737



J4739-10W

	Size	Product #	Tip Thickness (in)	Bit Length (in)	Overall Length (in)	Weight (lbs)
Slotted	1/4"	<b>J4743</b>	3/64	-	1-3/16	0.05
	3/16"	<b>J4744</b>	1/32	-	1-53/64	0.05
	1/4"	<b>J4745</b>	3/64	-	1-53/64	0.06
Phillips	#1	<b>J4737</b>	-	-	1-13/64	0.04
	#2	<b>J4738</b>	-	-	1-13/64	0.05
Torx®	T10	<b>J4739-10W</b>	-	5/8	1-1/2	0.06
	T15	<b>J4739-15W</b>	-	5/8	1-1/2	0.05
	T20	<b>J4739-20W</b>	-	5/8	1-1/2	0.05
	T25	<b>J4739-25W</b>	-	5/8	1-1/2	0.05
	T27	<b>J4739-27W</b>	-	5/8	1-1/2	0.06
	T30	<b>J4739-30W</b>	-	7/8	1-3/4	0.05



## 1/4" DRIVE BALL END HEX BIT SOCKETS

- Full polish sockets meet and exceed stringent aerospace specification AS4984A which requires tools to have a thicker nickel-chrome coating for greater corrosion-resistance and durability.



INCH	HEX	Overall Length (in)	Weight (lbs)
1/4	<b>J47701/4B</b>	1-1/2	0.05
1/8	<b>J47701/8B</b>	1-1/2	0.05
3/16	<b>J47703/16B</b>	1-1/2	0.05
3/32	<b>J47703/32B</b>	1-1/2	0.05
5/32	<b>J47705/32B</b>	1-1/2	0.05
7/32	<b>J47707/32B</b>	1-1/2	0.05
7/64	<b>J47707/64B</b>	1-1/2	0.05
9/64	<b>J47709/64B</b>	1-1/2	0.05



## 1/4" DRIVE HEX BIT SOCKETS

INCH	HEX	Bit Length (in)	Overall Length (in)	Weight (lbs)
1/16	<b>J47701/16</b>	1	1-7/8	0.05
5/64	<b>J47705/64</b>	1	1-7/8	0.05
3/32	<b>J47703/32</b>	1	1-7/8	0.05
7/64	<b>J47707/64</b>	1	1-7/8	0.06
1/8	<b>J47701/8</b>	1	1-7/8	0.05
9/64	<b>J47709/64</b>	1	1-7/8	0.05
5/32	<b>J47705/32</b>	1	1-7/8	0.05
3/16	<b>J47703/16</b>	1	1-7/8	0.05
7/32	<b>J47707/32</b>	1	1-7/8	0.05
1/4	<b>J47701/4</b>	1	1-7/8	0.06
5/16	<b>J47705/16</b>	1	1-7/8	0.06



- Bit holders have a hex opening to hold the bit allowing the bit holder to take the full load of torque.
- Made of heat-treated alloy steel.
- Polished chrome finish on socket.



MM	HEX	Bit Length (in)	Overall Length (in)	Weight (lbs)	Repair Kit Part #
2	<b>J4770-2M</b>	1	1-7/8	0.04	-
2.5	<b>J4770-2.5M</b>	1	1-7/8	0.05	J4770-2.5MRKA
3	<b>J4770-3M</b>	1	1-7/8	0.05	J4770-3MRKA
4	<b>J4770-4M</b>	1	1-7/8	0.05	J4770-4MRKA
5	<b>J4770-5M</b>	1	1-7/8	0.05	-
6	<b>J4770-6M</b>	1	1-7/8	0.05	-



1/4" DRIVE BIT SOCKETS