



## 3/8" DRIVE TORX® IMPACT SOCKETS

- › Made of heat-treated alloy steel.
- › Socket size stamped on tool for easy identification.
- › Side locking hole.
- › For use with Torx® style fasteners.

| Torx® Size |                | Overall Length (in) | Weight (lbs) |
|------------|----------------|---------------------|--------------|
| E6         | <b>J7206TX</b> | 1-1/4               | 0.06         |
| E7         | <b>J7207TX</b> | 1-1/4               | 0.07         |
| E8         | <b>J7208TX</b> | 1-1/4               | 0.07         |
| E10        | <b>J7210TX</b> | 1-1/4               | 0.07         |
| E12        | <b>J7212TX</b> | 1-1/4               | 0.07         |
| E14        | <b>J7214TX</b> | 1-1/4               | 0.09         |
| E16        | <b>J7216TX</b> | 1-1/4               | 0.10         |



3/8" DRIVE IMPACT SOCKETS

## 3/8" DRIVE IMPACT HEX BIT SOCKETS

- › Proto® Hex Bit Impact Sockets can be used on stubborn fasteners.
- › Tight tolerances for snug fit on fastener.
- › Hex bit impact sockets are used wherever powered drive tools are used to install or remove fasteners.
- › Hex bit impact sockets are designed to withstand the high torque and force associated with impact tools in repetitive application.
- › Side locking hole.

| INCH |                  | Bit Length (in) | Overall Length (in) | Weight (lbs) |
|------|------------------|-----------------|---------------------|--------------|
| 1/8  | <b>J72901/8</b>  | 1-5/8           | 2-23/32             | 0.07         |
| 5/32 | <b>J72905/32</b> | 1-5/8           | 2-23/32             | 0.08         |
| 3/16 | <b>J72903/16</b> | 1-5/8           | 2-23/32             | 0.08         |
| 7/32 | <b>J72907/32</b> | 1-5/8           | 2-23/32             | 0.09         |
| 1/4  | <b>J72901/4</b>  | 1-5/8           | 2-23/32             | 0.10         |
| 5/16 | <b>J72905/16</b> | 1-5/8           | 2-23/32             | 0.13         |
| 3/8  | <b>J72903/8</b>  | 1-5/8           | 2-23/32             | 0.14         |



| MM |                  | Bit Length (in) | Overall Length (in) | Weight (lbs) |
|----|------------------|-----------------|---------------------|--------------|
| 4  | <b>J7290-4M</b>  | 1-5/8           | 2-23/32             | 0.07         |
| 5  | <b>J7290-5M</b>  | 1-5/8           | 2-23/32             | 0.08         |
| 6  | <b>J7290-6M</b>  | 1-5/8           | 2-23/32             | 0.09         |
| 8  | <b>J7290-8M</b>  | 1-5/8           | 2-23/32             | 0.12         |
| 10 | <b>J7290-10M</b> | 1-5/8           | 2-23/32             | 0.14         |

