




## 1/2" DRIVE DEEP UNIVERSAL IMPACT SOCKETS - 6 POINT

- › Ball and spring design which allows for a 30° working angle.
- › Smooth 360° rotation.
- › Proto® 6 Point Impact Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.



- › Radius-corner socket design
- › Engages flats for better grip
- › Improves the ability to turn worn or rounded fasteners

1/2" DRIVE IMPACT SOCKETS

INCH	6	Drive End Outside Diameter (in) (C)	Nut Depth (in) (D)	Bolt Clearance Depth (in) (E)	Overall Length (in) (L)	Weight (lbs)
1/2	<b>J75275P</b>	1-1/16	11/16	1-5/8	3-9/16	0.41
9/16	<b>J75276P</b>	1-1/16	11/16	1-5/8	3-9/16	0.43
5/8	<b>J75277P</b>	1-1/16	11/16	1-21/32	3-9/16	0.45
11/16	<b>J75278P</b>	1-1/4	11/16	1-21/32	3-1/2	0.50
3/4	<b>J75279P</b>	1-1/4	11/16	1-39/64	3-1/2	0.55
13/16	<b>J75280P</b>	1-1/4	11/16	1-5/8	3-1/2	0.61
7/8	<b>J75281P</b>	1-1/4	11/16	1-5/8	3-1/2	0.73
15/16	<b>J75282P</b>	1-3/8	11/16	1-43/64	3-23/32	0.80

ASME B107.110-2012

MM	6	Drive End Outside Diameter (in) (C)	Nut Depth (in) (D)	Bolt Clearance Depth (in) (E)	Overall Length (in) (L)	Weight (lbs)
13	<b>J75413MP</b>	1-1/16	11/16	1-5/8	3-1/2	0.43
14	<b>J75414MP</b>	1-1/16	11/16	1-5/8	3-1/2	0.45
15	<b>J75415MP</b>	1-1/16	11/16	1-5/8	3-1/2	0.50
16	<b>J75416MP</b>	1-1/16	11/16	1-5/8	3-1/2	0.55
17	<b>J75417MP</b>	1-1/4	11/16	1-5/8	3-1/2	0.61
18	<b>J75418MP</b>	1-1/4	11/16	1-5/8	3-1/2	0.73
19	<b>J75419MP</b>	1-1/4	11/16	1-5/8	3-1/2	0.80

ASME B107.110-2012

## 1/2" DRIVE IMPACT UNIVERSAL JOINT

- › Tight tolerances for snug fit on fastener.
- › Used wherever powered drive tools are used to install or remove fasteners.
- › Designed to withstand the high torque and force associated with impact tools in repetitive application.
- › Position at appropriate angle to turn fasteners where obstructions prevent a straight application.
- › Ball and spring design which allows for a 30° working angle.
- › Smooth 360° rotation.



Product #	Overall Length (in)	Weight (lbs)
<b>J74470P</b>	2-19/32	0.57

ASME B107.110-2012