


## SHORT SATIN ANGLE OPEN END WRENCHES

- › Satin finish provides corrosion resistance and a slip resistant grip.
- › 15° and 75° angle heads allow wrench to be used in four different turning angles for greater access in tight work spaces.
- › Compact shank design and short length for access in confined spaces.
- › Standard open end configuration.



INCH		Throat Depth 1 (in)	Outside Head Width 1 (in)	Head Thickness 1 (in)	Outside Head Width 2 (in)	Head Thickness 2 (in)	Overall Length (in)	Weight (lbs)
7/32	<b>J3314</b>	11/64	1/2	1/8	1/2	7/64	3	0.03
15/64	<b>J3315</b>	11/64	1/2	1/8	1/2	7/64	3	0.03
1/4	<b>J3316</b>	11/64	1/2	1/8	1/2	7/64	3	0.03
9/32	<b>J3318</b>	3/16	19/32	5/32	19/32	5/32	3-1/2	0.04
5/16	<b>J3320</b>	3/16	19/32	5/32	19/32	5/32	3-1/2	0.04
11/32	<b>J3322</b>	1/4	3/4	5/32	3/4	5/32	3-3/4	0.05
3/8	<b>J3324</b>	1/4	3/4	5/32	3/4	5/32	3-3/4	0.05
7/16	<b>J3328</b>	11/32	1	3/16	1	11/64	4-7/16	0.08
1/2	<b>J3332</b>	11/32	1	3/16	1	11/64	4-7/16	0.08
9/16	<b>J3336</b>	13/32	1-5/32	3/16	1-5/32	3/16	5-3/4	0.10
5/8	<b>J3340</b>	13/32	1-5/32	3/16	1-5/32	3/16	5-3/4	0.10




## FACOM® SHORT SATIN METRIC ANGLE OPEN END WRENCHES



- › Satin finish provides corrosion resistance and slip resistant grip.
- › 15° and 75° angled heads for fasteners out of standard tool reach.
- › Short shanks and slim heads.
- › Standard open end configuration.



MM		Outside Head Width 1 (in)	Head Thickness 1 (in)	Outside Head Width 2 (in)	Head Thickness 2 (in)	Overall Length (in)	Weight (lbs)
3.2	<b>34.3.2</b>	25/64	3/32	25/64	3/32	2-3/4	0.01
4	<b>34.4</b>	25/64	3/32	25/64	3/32	2-3/4	0.01
5	<b>34.5</b>	33/64	3/32	33/64	3/32	2-61/64	0.02
5.5	<b>34.5.5</b>	33/64	1/8	33/64	7/64	2-61/64	0.02
6	<b>34.6</b>	19/32	1/8	19/32	7/64	3-5/32	0.02
7	<b>34.7</b>	19/32	1/8	19/32	1/8	3-5/32	0.02
8	<b>34.8</b>	47/64	1/8	47/64	1/8	3-35/64	0.04
9	<b>34.9</b>	47/64	1/8	47/64	1/8	3-35/64	0.04
10	<b>34.10</b>	55/64	1/8	55/64	1/8	3-15/16	0.05
11	<b>34.11</b>	55/64	1/8	55/64	1/8	3-15/16	0.05
12	<b>34.12</b>	1-1/16	5/32	1-1/16	9/64	3-15/16	0.08
13	<b>34.13</b>	1-1/16	5/32	1-1/16	9/64	4-23/32	0.08
14	<b>34.14</b>	1-1/16	5/32	1-1/16	9/64	4-23/32	0.08
15	<b>34.15</b>	1-19/64	3/16	1-19/64	11/64	5-33/64	0.15
16	<b>34.16</b>	1-19/64	3/16	1-19/64	11/64	5-33/64	0.14
17	<b>34.17</b>	1-19/64	3/16	1-19/64	11/64	5-33/64	0.14