FACOM® SATIN PIN REPLACEMENTS - SQUARE



- > Satin finish provides corrosion resistance and a slip-resistant grip.
- ▶ Interchangeable pins are easy to swap out.

Pin					
MM	Product #	Diameter (in)	Height (in)	Weight (lbs)	
4	118.EC4	5/32	19/32	0.02	
5	118.EC5	6/32	3/8	0.02	
8	118.EC8	10/32	3/8	0.03	



FACOM® HINGED HOOK SPANNER WRENCHES



Joint fitted with a spring washer for smooth, reliable operation.





MM	Product #	Maximum Opening (in)	Head Thickness 1 (in)	Hook Thickness (in)	Height (in)	Overall Length (in)	Weight (lbs)
15-35	125A.35	1-1/2	13/64	1/8	5/16	6-39/64	0.17
35-50	125A.50	1-31/32	15/64	5/32	7/16	7-61/64	0.37
50-80	125A.80	3-5/32	5/16	13/64	7/16	11-1/32	0.83
80-120	125A.120	4-23/32	23/64	7/32	15/32	13-37/64	1.54
120-180	125A.180	7-3/32	7/16	19/64	15-15/16	19-3/8	3.26

FACOM® HEAVY DUTY HOOK SPANNER WRENCHES



- 11-hole adjustment.
- Forged hook, hardened to 44 HRc.



MM	Product #	Hook Thickness (in)	Overall Length (in)	Weight (lbs)
120-224	119.3/8	24	6.96	7.28
220-324	119.3/4	26	13.01	12.27



ADJUSTABLE HOOK SPANNER WRENCHES

- Non-reflective black oxide finish for use where non-plated products are required.
- Use to tighten side slot nuts on collars, lock nuts and bearings





		Hook		Overall	
Product #	Capacity Range	Thickness (in)	Hook Depth (in)	Length (in)	Weight (lbs)
JC471	3/4 to 2	11/32	1/8	6-3/8	0.23
JC472	1-1/4 to 3	13/32	5/32	8-1/8	0.43
JC474	2 to 4-3/4	15/32	3/16	11-3/8	1.03
JC474A	4-1/2 to 6-1/4	15/32	1/4	12-1/8	1.07
JC474B	6-1/8 to 8-3/4	15/32	5/16	13-3/4	1.40









