



ADJUSTABLE OIL FILTER PLIERS

- ▶ Heavy-duty forged jaws with three contact points to grip stubborn oil filters.
- ▶ Textured grips for non-slip operation.



Product #	Opening Range (in)	Diameter Minimum (in)	Diameter Maximum (in)	Diameter Minimum (mm)	Diameter Maximum (mm)	Height (in)	Overall Length (in)	Weight (lbs)
JFF297	2-1/4 to 5	2-1/4	5	57	127	19/32	13-19/32	1.25
JFF287	3-3/4 to 7	3-3/4	7	94	178	1	19	3.28

ALL-PURPOSE BRAKE PLIERS

- ▶ Easily installs and removes brake shoe retaining spring on drum brakes.
- ▶ Socket end removes spring from anchor stud.
- ▶ Notched and installs spring on anchor.



Product #	Overall Length (in)	Weight (lbs)
J217	12-7/8	1.05



LOCK RING "HORSESHOE" WASHER PLIERS

- ▶ For spreading both soft iron "horseshoe" lock washers used on brakes and tempered steel lock rings used on gear and bearing shafts.
- ▶ Plastisol grips for added comfort.



Product #	Overall Length (in)	Weight (lbs)
J2506	9	0.49



LOCK RING PLIERS - PARALLEL JAW

- ▶ For removal of lock snap rings used on bearing shafts.
- ▶ Compound leverage simplifies removal.
- ▶ Jaw tips are indented to hold ring ends and prevent breakage.
- ▶ Jaws spread 1-1/4".
- ▶ Plastisol grips for added comfort.



Product #	Overall Length (in)	Weight (lbs)
J2516	10-9/16	0.68

