

RETAINING RING PLIERS - CONVERTIBLE

- › Converts from internal to external or vice versa, when pivot screw is moved to adjacent tapped hole.
- › Use with either External or Internal Retaining Rings.
- › Fixed tips are precision formed and induction hardened for accurate fit and long wear.
- › Use the largest diameter tip that will fit the retaining ring being removed or installed.



Product #	Tip Size	Tip Angle	Overall Length (in)	Shaft Dia. (in) (External)	Bore Dia. (in) (Internal)	Weight (lbs)
J399	0.038	0°	5-7/8	1/4 - 43/64	3/8 - 9/16	0.15
J370	0.038	45°	5-3/4	1/4 - 3/64	3/8 - 9/16	0.16
J371	0.038	90°	5-11/16	1/2 - 25/32	3/8 - 9/16	0.16
J372	0.047	0°	5-7/8	11/16 - 7/8	5/8 - 1	0.16
J373	0.047	45°	5-3/4	11/16 - 7/8	5/8 - 1	0.15
J374	0.047	90°	5-11/16	13/16 - 1	5/8 - 1	0.16
J385	0.070	0°	7-1/2	15/16 - 1-7/16	1-1/16 - 1-3/4	0.29
J375	0.070	45°	7-3/8	1 - 1-7/16	1-1/16 - 1-3/4	0.32
J376	0.070	90°	7-1/8	1 - 1/16, 2	1-7/16 - 2	0.31
J377	0.090	0°	9-1/4	1-1/2 - 3-1/2	1-13/16 - 3	0.54
J378	0.090	45°	9	1-1/2 - 3-1/2	1-13/16 - 3	0.55
J379	0.090	90°	8-5/8	1-1/2 - 1-3/4	1-13/16 - 3	0.56
J399L	0.038	18°	6	-	3/8 - 9/16	0.19
J371L	0.038	90°	6	-	3/8 - 9/16	0.19
J385L	0.070	18°	7-1/4	-	1-1/16 - 1-3/4	0.33
J376L	0.070	90°	7-1/4	-	1-7/16 - 2	0.33

ASME B107.19 

RETAINING RING PLIERS - EXTERNAL

- › Used with External Retaining Rings.
- › Fixed tips are precision formed and induction hardened for accurate fit and long wear.



Product #	Tip Size	Tip Angle	Overall Length (in)	Shaft Dia. (in) (External)	Weight (lbs)
J388*	0.023	0°	5-1/4	3/16 - 15/64	0.06
J391	0.038	0°	6-1/8	1/4 - 21/32	0.15
J397	0.038	90°	6-1/8	1/4 - 1	0.15
J393	0.070	0°	6-7/8	7/16 - 2	0.22
J395	0.115	0°	9-1/8	1-1/2 - 3-1/2	0.49

*No Grip. Applies only to J388.

ASME B107.19 