# **FLEET MAINTENANCE**

# B

FLUID SERVICE TOOLS

## **OIL FILTER WRENCHES**

- > Handle swivels to avoid obstructions.
- > Stainless steel band for added strength.

Product #	Diameter Minimum (in)	Diameter Maximum (in)	Overall Length (in)	Weight (lbs)
<b>J3007</b>	2-7/8	3-1/4	8	0.81
<b>J3006</b>	3-1/2	3-7/8	8-1/2	0.81
<b>J3008</b>	4-1/8	4-1/2	9-1/2	0.88



#### SWIVEL OIL FILTER WRENCH

- Stainless steel band with projection welds for strength and anti-corrosion.
- > Heat-treated swivel handle adjusts to a wide arc of positions.
- Minimum grip: 4-1/8" (104.7 mm).
- Maximum grip: 4-7/16" (112.7 mm).
- > Over 150 foot pounds of torque.



Product #	Diameter Minimum (in)	Diameter Maximum (in)	Diameter Minimum (mm)	Diameter Maximum (mm)	Height (in)	Overall Length (in)	Weight (lbs)
JFF5325A	4-1/8	4-7/16	104.7	112.7	1	10	0.65

### ADJUSTABLE OIL FILTER PLIERS

- Heavy-duty forged jaws with three contact points to grip stubborn oil filters.
- > Textured grips for non-slip operation.



Product #	Opening Range (in)	Diameter Minimum (in)	Diameter Maximum (in)	Diameter Minimum (mm)	Diameter Maximum (mm)	Height (in)	Overall Length (in)	Weight (lbs)
JFF297	2-1/4 to 5	2-1/4	5	57	127	19/32	13-19/32	1.25
JFF287	3-3/4 to 7	3-3/4	7	94	178	1	19	3.28