STANLEY® FATMAX® STUD SENSOR 300

Backlit LCD screen clearly displays all of the sensor's readings, even in low light conditions.

Battery Needs

1

- Wood and metal stud detection through up to 1-1/2" deep surface material.
- AC detection identifies live wires up to 2" deep.
- OnePass[™] Center-Find Technology locates stud centers.
- Deep metal scan senses metal through up to 3" of material.
- Auto calibration.
- e accuracy of marking-out readings.
- p buttons provide comfort and control.



Width (in)

3-1/2

Scan Depth (in)

1-1/2

Height (in)

1-1/2

 Marking channel helps improve acc Ergonomic design and soft grip but 					
Product #	Overall Length (in				
FMHT77407	6-1/2				

STANLEY® STUD SENSOR 200

- LCD screen clearly displays all of the sensor's readings.
- Wood and metal stud detection through up to 1-1/2" deep surface material.
- AC detection identifies live wires up to 2" deep.
- OnePass[™] Center-Find Technology locates stud centers.
- Marking channel helps improve accuracy of marking-out readings.
- Ergonomic design and soft grip buttons provide comfort and control.



Product #	Overall Length (in)	Battery Needs	Battery Type	Height (in)	Width (in)	Scan Depth (in)
STHT77406	5-5/8	1	9V	1-3/8	3	3/4
STHT77587	5-3/4	1	9V	1-3/8	3	1/2, 1 ,1-1/2

Battery Type

9V

STANLEY® STUD SENSOR 150

- Wood and metal stud detection through up to 1-1/2" below surface material.
- AC detection identifies live wires up to 2" deep.
- Sequential LEDs and audible beeps indicates reading.
- Marking channel with LED identifies target and makes marking surfaces easy and accurate.
- Ergonomic design and soft grip buttons provide comfort and control.



Product #	Overall Length (in)	Battery Needs	Battery Type	Height (in)	Width (in)	Scan Depth (in)
STHT77404	5-3/4	1	9V	1-3/8	2-7/8	1-1/2
STHT77588	7	2	AAA	1	4	1-1/2