

FACOM® INSULATED VSE HACKSAW



- › Two blade positions.
- › Butterfly tension nut.
- › Supplied with bi-metal blade.
- › 12" blade replacement.

Product #	Blade Length (in)	Overall Length (in) (L)	Weight (lbs)
FT-602.AVSE	12	18-1/2	1.30



C-CLAMPS - HEAVY SERVICE STANDARD SCREW

- › Designed for heavy service applications where the strength of the extra heavy service C-clamp is not required.
- › Clamps have a high-strength steel frame with a hardened forcing screw.
- › Forcing screws are fitted with impact resistant pads.



Product #	Opening Range (in) (C)	Throat Depth (in) (T)	Thread Diameter (in) (D)	Minimum Test Load (lbs)	Weight (lbs)
J102GS	0-2	1-3/8	1/2	7500	1.30
J103GS	0-3	1-3/4	5/8	8750	2.60
J104GS	0- 4-1/8	2	3/4	10000	4.10
J106GS	2-6	2-1/4	3/4	11250	5.90
J108GS	4-8	2-1/4	3/4	12500	6.90
J110GS	6- 10-1/4	2-3/8	3/4	13750	8.00
J112GS	8-12	2-5/8	7/8	15000	11.6
J115GS	10-15	2-5/8	7/8	16250	15.0
J118GS	12-18	2-7/8	7/8	17500	18.2



C-CLAMPS - STANDARD SERVICE DEEP THROAT FULL LENGTH SCREW

- › Standard service, deep throat style is the most versatile and popular.
- › Hot forged for strength and hard use.
- › Forcing screw has heavy rolled Acme thread allowing the screw to turn easily under pressure and is less susceptible to damage.
- › Forcing screw has a sliding T-handle and an impact resistant pad.



Product #	Opening Range (in) (C)	Throat Depth (in) (T)	Thread Diameter (in) (D)	Minimum Test Load (lbs)	Weight (lbs)
J402	0-2	2	1/2	3500	1.30
J403	0-3	2-3/8	1/2	3500	2.00
J404	0-4	2-3/4	3/4	6500	3.50
J406	0-6	3-5/8	3/4	6600	5.00
J408	0-8	4-1/2	3/4	6900	7.00
J410	0-10	5-3/8	3/4	8000	10.5
J412	0-12	5-3/4	7/8	9500	15.5

