



## C-CLAMPS - STANDARD SERVICE DEEP THROAT SPATTER RESISTANT FULL LENGTH SCREW

- › Forcing screw and pad are plated with copper to resist welding spatter.
- › Hot forged for strength and hard use.
- › Forcing screw has heavy rolled Acme thread allowing the screw to turn easily under pressure and is less susceptible to damage.
- › Forcing screw has a sliding T-handle and an impact resistant pad.



C-CLAMPS

Product #	Opening Range (in) (C)	Throat Depth (in) (T)	Thread Diameter (in) (D)	Minimum Test Load (lbs)	Weight (lbs)
<b>J402S</b>	0-2	2	1/2	3300	1.30
<b>J403S</b>	0-3	2-3/8	1/2	3500	2.00
<b>J404S</b>	0-4	2-3/4	3/4	4100	3.50
<b>J406S</b>	0-6	3-5/8	3/4	5400	5.00
<b>J408S</b>	0-8	4-1/2	3/4	5900	7.00
<b>J410S</b>	0-10	5-3/8	3/4	6200	10.5
<b>J412S</b>	0-12	5-3/4	7/8	9300	15.5



## C-CLAMPS - STANDARD SERVICE EXTRA DEEP THROAT SPATTER RESISTANT FULL LENGTH SCREW

- › Forcing screw and pad are plated with copper to resist welding spatter.
- › Up to 32% more throat depth than standard deep throat clamps.
- › Hot forged for strength and hard use.
- › Forcing screw has heavy rolled Acme thread.
- › Full length forcing screw.



Product #	Spatter-Resistant	Opening Range (in) (C)	Throat Depth (in) (T)	Thread Diameter (in) (D)	Minimum Test Load (lbs)	Weight (lbs)
<b>J424</b>	<b>J424S</b>	0-4	3-5/8	3/4	4100	4.80
<b>J426</b>	<b>J426S</b>	0-6	4-3/4	3/4	5400	7.00
<b>J428</b>	<b>J428S</b>	0-8	5-5/8	3/4	5900	9.80

