NDICATOR ACCESSORIES

AGD INDICATOR ACCESSORIES

25SC SPLIT COLLETS

ENGLISH AND METRIC THREADS

For mounting AGD Indicators with 3/8" (9.5 mm) or 8 mm stems in gaging and work location fixtures, these collets simplify fixture mounting. Screw the collet into the fixture or into our 648 Depth Gage Base, insert the indicator into the collet and tighten it in place with the hexagonal nut. Internal collet fingers grip the stem with equal pressure to eliminate spindle binding. Made of steel with black finish. Overall length of collet and threads is 1".

25SC Split	Collets E	nglish Thread							
Cat. No.	EDP	Thread Size	Thread Length	Hole for Indicator Stem					
25SC14 25SC38	50155 50156	3/8-24NF 1/2-20NF	9/32" (7mm)	.375" (9.5mm) Diameter to 1/2" (12.7mm) depth; 1/4" (6.3mm) Diameter through hole .375" (9.5mm) Diameter through hole					
25SC38B	55995	1/2-32UN		.375" (9.5mm) Diameter through hole					
25SC Split Collets Metric Thread									
Cat. No.	EDP	Thread Size	Thread Length	Hole for Indicator Stem					
25SC8M	64885	M12 x 1.75	7mm	8mm Diameter through hole					

Split Bushings for 80 Miniature Dial Indicators

Length

Length

Length

12.7mm

1/2"

1/2"

EDP

EDP

EDP

56007

50154

56008

Split Bushings for AGD English Indicators

Split Bushings for AGD Metric Indicators

Cat. No.

Cat. No.

Cat. No.

25MSB

648-8

25SB

80SB

Diameter

Diameter

Diameter

Inside

8mm

Outside

Outside

Outside

9.5mm

200

.500"

.375"

Inside

.219"

Inside

.375"



Split Bushing Attachment



Threaded Stem Attachment



			1.
648 Depth Gage	Bases with Sten		
		Base Size	
Cat. No.	EDP	in	mm
648-4	65850	4	100
648-6	65851	6	150
	648 Depth Gage Cat. No. 648-4	648 Depth Gage Bases with StemCat. No.EDP648-465850	648-4 65850 4

8

LONG STEM DIAL INDICATORS

65852

648 DEPTH GAGE BASES WITH STEM COLLET Depth gage base with 25SC38 Stem Collet to fit 3/8" (9.5mm) stem dia. (as per AGD). Split bushings for adapting

is furnished unless otherwise specified.

THREADED STEMS

25LC RANGE LIMIT CAP

The Range Limit Cap replaces the stem cap furnished on most 81, 25, 2600, 655 and 656 AGD Indicators, preventing the possible error of a complete revolution. It can be adjusted to limit an indicator's measuring range any amount up to 3/8" (9.5mm).

Threaded stems on Starrett indicators with a .375"

(9.5mm diameter stem up to 1" (25mm) range (except long stem models) are available at additional cost. A

threaded stem is often desirable for attaching the

indicator to machine tools or fixtures. A 3/8-24 thread

25LC 50152	Part No.	EDP	
	25LC	50152	
	25LC	50152	

25LC Range Limit Cap

Starrett 81, 25, 2600, 655 and 656 Indicators through the 1" (25mm) range can be furnished with long stems up to 12" (300mm). These are especially useful for gaging in deep holes or where obstructions prevent the use of regular indicators. Specify stem length from outside case diameter when ordering.

Long stems not available on 80 Miniature Dial Indicators.



INDICATORS AND GAGES

starrett com

167



Range Limit Cap