

### Features

- Durable high gloss finish.
- Above-floor-drain (AFD) rough-in.
- In-tub removable seat mounts directly to the back of the bath and rests on the apron.
- 17-1/4" (438 mm) bath depth (floor to top of threshold).
- 60" (1524 mm) x 30" (762 mm) complete unit finished dimensions.

## Material

Compression molded from our exclusive Vikrell® material.

#### Installation

• Bath only installation not recommended. Must be used with STERLING wall set.



60" x 30" ADA Bath



Accord®



# ADA

**Codes/Standards** CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 Greenguard UL 2818 - Gold ADA

Warranty – Bathing Fixtures (and) Kitchen and Utility Sinks Made of Solid Vikrell<sup>®</sup> Material STERLING<sup>®</sup> Warranty - Bathing & Showering Seats See website for detailed warranty information.

# **Available Color/Finishes**

Color tiles intended for reference only.

**Color Code Description** 

Nhite

**KOHLER Biscuit** 96



Accord® 60" x 30" ADA Bath 71141114

No image available. This product is a component and not intended to be a standalone installation.

#### **Technical Information**

All product dimensions are nominal.Installation:3-Wall AlcoveDrain location:LeftBasin area, bottom:46-1/4" x 20-1/2" (1175 mm x 521 mm)Basin area, top:52-1/4" x 22-1/2" (1327 mm x 572 mm)Door width required:56-1/2" (1435 mm)

#### Notes

Install this product according to the installation instructions.

Product is designed to be used with a single-hole mixer valve with an escutcheon cover not to exceed 7-3/4" (197 mm) in width.

Bath cannot be installed without the wall surround.

Width of back wall at top transitions from 60" (1524 mm) at the front to 59-3/8" (1508 mm) in the back corners. Furring strips approximately 1/4" (6 mm) thick should be used at the back corner studs if drywall is to be installed over the nailing flange.

ADA compliant when installed to the specific requirements of these regulations.