

QULD-3322 Granite Undermount Low Divide Double Bowl Kitchen Sink

Manufactured from Quartz


(See page 2 for detailed information.)


Recommended for high-use traffic areas and commercial surfaces.

WARRANTY
Limited Lifetime – Residential
Limited 10-year – Commercial

FEATURES

- Low divider provides functionality of a single bowl with practicality of a double bowl.
- Made with 80% guartz stone, only a diamond is harder.
- Virtually indestructible, will not damage from kitchen use.
- Standard size is ideal for remodeling or new construction.
- Mounts under most countertop materials including granite, quartz, solid surface and tile.





Capacity: 10 gallons in left bowl, 7 gallons in right bowl

SPECIFICATIONS

QULD-3322 Granite Undermount Low Divide Double Bowl Kitchen Sink

Model	Part	Nominal Dimensions	Ship Wt. Lb.		Carton Dims. In.	Cu. Ft.
QULD-3322	QU03322LD	32" W x 21" D (813 mm x 533 mm)	48	FedEx	37 X 25 X 13	6.96

COLORS

(See inside back cover for color sample.)

- Espresso (170)
- Granito (076)
- Metallico (173)
- Nero (077)

MAINTENANCE AND CLEANING INFORMATION

Clean your Swan Granite Sink by using warm water and a soft clean cloth, or sponge. Non-abrasive liquid cleaners and detergents can also be used. Hard water, calcium and lime deposits can be removed with white vinegar on a paper towel and rinsing after 20 minutes. To restore luster and extend time between cleanings Granite Cleaner & Polish is recommended. Staining liquids, such as dyes and vegetable juices should be rinsed off as soon as possible. **Do not** use abrasive cleaners, metal-scouring pads, and bleach or alkali cleaners, such as ammonia.

STANDARDS AND RATINGS

American National Standard Institute—ANSI Z124.6 International Association of Plumbing and Mechanical Officials (IAPMO) – listed cUPC listed – Certified to CSA Standard B45 by IAPMO Heat resistance to 392°F, 200°C

SUPPORT DOCUMENTS

Installation instructions available at swanstone.com.

Undermount clips sold separately. Faucet options are limited to available hole placement. Please contact your dealer for more information.