

## Neorest 700H Elongated Toilet/Bidet

## FEATURES

- Tornado Flush™ siphon jet flushing system, ultra-high efficiency (1.0GPF/3.8LPF and 0.8GPF/3.0LPF).
- CeFiONtect™ ceramic glaze minimizes debris, mold and bacteria from sticking to porous, ceramic surfaces
- Dual flush function
- Universal height
- Auto lid open/close, auto flush
- eWater+
- Multifunctional remote control
- Adjustable heated seat
- Adjustable spray position
- Washlet with three wash modes (front, rear, soft)
- Oscillating and pulsing comfort washing
- Energy saver timer
- Built-in air purifying system
- Back-up manual flush
- ADA Compliant

## COMPONENTS

- SN992M - Top Unit
- CT992CUMFG - Elongated Bowl

Note: SN992M Only compatible with CT992CUMFG

## COLORS/FINISHES

- #01 Cotton

## PRODUCT SPECIFICATION

The Neorest 700H with the Tornado Flush flushing system toilet shall be 1.0GPF/3.8LPF and 0.8 GPF/3.0 LPF. Toilet shall have CeFiONtect ceramic glaze and be at Universal Height. Toilet shall be of skirted design, elongated front bowl with auto open and close seat. Toilet shall be **TOTO Model MS992CUMFG**.



eWater+

 CeFiONtect

 Tornado Flush

## CODES/STANDARDS

- Meets and exceeds ASME A112.4.2, ASME A112.19.2/CSA B45.1, ASME A112.18.1/CSA B125.1, UL 1431, CSA C22.2 # 68
- Certifications: IAPMO(cUPC), State of Massachusetts, City of Los Angeles and others
- Code Compliance: UPC, IPC, NSPC, and others
- ADA Compliant



# MS992CUMFG

## Neorest 700H Elongated Toilet/Bidet

### SPECIFICATIONS

|                           |  |
|---------------------------|--|
| Water Use:                | 1.0 GPF/3.8 LPF<br>& 0.8 GPF/3.0 LPF   |
| Flush System:             | Tornado Flush Siphon Jet   |
| Water Pressure:           | Min 7 PSI (0.05MPa) Flowing<br>Max 105 PSI (0.75 MPa) Static   |
| Min Flow Rate:            | 2.64 gal/min (10 L/min)  |
| Water Surface:            | 8-3/4" x 7-1/4"  |
| Trap Diameter:            | 2-1/8" (54 mm)   |
| Rough In:                 | 12" rough in<br>Warning: If there is a base board in the restroom, the center of the floor drain should be a minimum of 12" from the base board. |
| Trap Seal:                | 2-1/16" (53 mm)  |
| Warranty:                 | Three Year Limited (Residential)<br>One Year Limited (Commercial)  |
| Material:                 | Bowl: Vitreous china<br>Seat and cover: Plastic  |
| Shipping Weight:          | Top Unit - SN992M 17.6lbs<br>Bowl Unit - CT992CUMFG 106lbs   |
| Shipping Dimensions:      | SN992M -<br>20-5/8" x 34-13/16" x 8-13/16"<br>CT992CUMFG -<br>18-13/16" x 33-1/4" x 24-7/8"  |
| Power Rating              | 120V AC, 60 Hz. 1300W  |
| Power Cord                | Maximum length: 4 ft (1.2 m)   |
| Water Feature             | Adjustable Water Flow Rate   |
| Rear Washing              | from 9.1 to 14.5 oz/min.   |
| Soft Washing              | from 10.8 to 14.5 oz/min.  |
| Front Washing             | from 9.8 to 14.5 oz/min.   |
| Wide Front Washing        | from 11.8 to 14.5 oz/min.  |
| Washing Spray Temperature | Minimum: 86° F/30° C<br>Maximum: 104° F/40° C  |
| Safety Feature            | Temperature fuse and float switch  |
| Drying Feature            | Air Temperature:<br>High: About 130°F/55°C<br>Low: About 95°F/35°C   |
| Capacity of Air           | 10.2 ft³/min   |
| Safety Feature            | Temperature fuse   |
| Seat Warming Feature      | Surface Temperature:<br>Minimum: 82° F/28° C<br>Maximum: 97° F/36° C   |
| Seat Heater Capacity      | 60W  |
| Safety Feature            | Thermal fuse   |
| Air Purifying Feature     | Method: O <sub>2</sub> Deodorizer<br>Air Volume: 5.7 ft³/min   |
| Ambient Temperature Range | 33°F/1°C to 104°F/40°C   |
| Product Size              | 17-5/18" x 31-7/16" x 20-3/4"  |
| Weight                    | Net: 123.6 lbs.  |
| Floor to Seat Height:     | 17 1/4" (438mm)  |

### INSTALLATION NOTES

- For use with potable water only. Do not use with recycled water.

