

Features

- \bullet 15" (381) x 1241/64" (321) x 7" (178) undermount bar or entertainment sink.
- Single compartment.
- 16 gauge 304 stainless steel.
- Center drain location.
- · Superior undercoating for added sound insulation.
- 3mm sound deadening pads on all 4 sink sides and bottom. Up to 3 times heavier than competitive models.
- Fits 18" base cabinet width.

Components

Product includes: **Cutout Template** Installation Hardware Installation Instructions

shown with Transolid T3530-LS faucet

Options

TSGM15131 Stainless Steel Bottom Sink Grid TCBM711 Bamboo Cutting Board 2210R Covered Sink Strainer or 4010 Covered Disposer Strainer


Warranty

Lifetime Limited Warranty



Specified Model

Model	MUSB15137
Overall	L15" x W12 ⁴¹ / ₆₄ " x D7"
Dimensions	381 x 321 x 178
Bowl Dimensions	L13¾" x W10¾" x D7" 333 x 273 x 178
- · · ·	
Drain hole:	35/4" (92mm)
Shipping Weight	15 lbs.
Material	16 gauge 304 stainless steel
Installation	under counter mounted
Required	template, included



Codes/Standards

ASME A112.19.3/CSA B45.4


Notes

Install this product according to the installation instructions.



Optional Accessories

TSGM15131 Bottom Sink Grid



2210R Covered Flip Top Sink Strainer.




Water drains easily when cover is in place. Cover flips up with easy touch. Cover makes a flat surface at the sink bottom that prevents food waste from getting into the strainer basket for easy sink clean up. Polypropylene housing. Fits standard 3½" opening.

4010 Covered Flip Top Disposer Strainer.



Water drains easily when cover is in place. Cover flips up with easy touch. Polypropylene housing. Top mount installation for 3½" opening.

2310 Remote Covered Flip Top Sink Strainer.



Turn the remote knob to open and close drain. Water drains easily when cover is in place. Cover flips up with easy touch.

Cover makes a flat surface at the sink bottom that prevents food waste from getting into the strainer basket for easy sink clean up.

Polypropylene housing. Fits standard 3½" opening. 1¾" hole required in countertop for remote installation. Remote cable 25½" L.