

Integral Bonnet Needle Valves


Part No.

SS-26VF8

Part Description


Stainless Steel Integral Bonnet Needle Valve, 0.73 Cv, 1/2 in. FNPT, Vee Stem


Specifications

| General | |
|--------------------------------------|---|
| Body Material | 316 Stainless Steel |
| Cleaning Process | Standard Cleaning and Packaging (SC-10) |
| Connection 1 Size | 1/2 in. |
| Connection 1 Type | Female NPT |
| Connection 2 Size | 1/2 in. |
| Connection 2 Type | Female NPT |
| eClass (4.1) | 37010201 |
| eClass (5.1.4) | 37010201 |
| eClass (6.0) | 37010203 |
| eClass (6.1) | 37010203 |
| Flow Pattern | Straight (2-way) |
| Handle Color | Not Applicable |
| Handle Style | Stainless Steel Bar |
| Lubricant | Perf. Polyether/Tung. Disulfide (WL7) |
| Max Temperature with Pressure Rating | 450°F @ 4130 PSIG /232°C @ 284 BAR |
| Orifice | 0.250 in |
| Packing | PFA |
| Room Temperature Pressure Rating | 6000 PSIG @ 100°F /413 BAR @ 37°C |
| Stem Tip Material | 316 Stainless Steel |
| Stem Type | Vee |
| UNSPSC (10.0) | 40141602 |
| UNSPSC (11.0501) | 40141602 |
| UNSPSC (13.0601) | 40141602 |
| UNSPSC (15.1) | 40141602 |
| UNSPSC (17.1001) | 40141600 |
| UNSPSC (4.03) | 40141602 |
| UNSPSC (PGE) | 401416AL |
| UNSPSC (SEQIRUS) | M4170 |
| UNSPSC (SWG01) | 40141602 |

Valve Material

Stainless Steel

 The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

 Caution: Do not mix or interchange valve components with those of other manufacturers.