

Victaulic® Drain Elbow No. 10-DR



Approvals/Listings



[See Victaulic publication 10.01 for details](#)

Product Description

No. 10-DR drain elbows are specifically designed for use on fire protection standpipes. The drain is drilled and tapped for a 1 1/25 mm NPT outlet.

Constructed of durable ductile iron all sizes conform to the ratings of Style 77 couplings. No.10-DR elbows are supplied with grooves or shoulders. These fittings are not intended for use with Victaulic Plain End couplings.

When connecting wafer or lug-type butterfly valves directly to Victaulic drain elbows with Style 741 or 743 Vic-Flange® Adapters or Style 744 FireLock® Flange Adapters, check disc clearance dimensions with the I.D. dimension of the fitting.

Material Specifications

Housing:

Ductile iron conforming to ASTM A-536, grade 65-45-12.

Housing Coating: (specify choice)

Standard: Orange enamel.

Optional: Hot dipped galvanized and others.

Job/Owner

System No.	
Location	

Contractor

Submitted By	
Date	

Engineer


Spec Section	
Paragraph	
Approved	
Date	

[Fittings](#) | [Elbow](#) | [No. 10-DR](#) | Publication 10.05

10.05 1509 Rev E Updated 11/2013 © 2013 Victaulic Company. All rights reserved.

Dimensions

No 10-DR



Fitting Size		Dimensions			Approximate Weight Each
Nominal Size	Actual Outside Diameter	C - E	H	P	
inches mm	inches mm	inches mm	inches mm	inches mm	lbs. kg
2 1/2 65	2.875 73.0	3.75 95	2.75 70	1.68 43	5.2 2.4
3 80	3.500 88.9	4.25 108	2.75 70	2.10 53	5.3 2.4
4 100	4.500 114.3	5.00 127	2.75 70	2.60 66	8.8 4.0
6 150	6.625 168.3	6.50 165	2.75 70	3.65 93	18.7 8.5

Installation

Reference should always be made to the [I-100 Victaulic Field Installation Handbook](#) for the product you are installing. Handbooks are included with each shipment of Victaulic products for complete installation and assembly data, and are available in PDF format on our website at www.victaulic.com.

Warranty

Refer to the Warranty section of the current Price List or contact Victaulic for details.

Note

This product shall be manufactured by Victaulic or to Victaulic specifications. All products to be installed in accordance with current Victaulic installation/assembly instructions. Victaulic reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligations.

Trademarks

Victaulic®, FireLock and Vic-Flange are registered trademarks of Victaulic Company.