



ViegaPEX tubing
Zero Lead
 - For installation between studs
 - PEX
 - ManaPac
Components
 Recycled plastic reels
Technical Data
 PEX designation code 5006
 Chlorine resistance rating CL5
 UV resistance 60 days
ASTM F876, ASTM F877
Model V5004

d	L [ft]	Reel(s)	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	2	red/blue	58.000	1	32300	1
3/8	500	1	blue	28.000	1	32905	1
3/8	500	1	red	28.000	1	32805	1
1/2	300	2	red/blue	48.000	1	32326	1
1/2	300	1	blue	23.100	1	32923	1
1/2	300	1	red	23.100	1	32823	1



ViegaPEX tubing
Zero Lead
 - PEX
 - Coil
Technical Data
 PEX designation code 5006
 Chlorine resistance rating CL5
 UV resistance 60 days
ASTM F876, ASTM F877
Model V5003

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/4	100	white	3.200	1	32011	1
1/4	500	white	14.000	1	32015	1
3/8	100	white	5.000	1	32001¹	1
3/8	500	white	21.000	1	32005¹	1
3/8	1000	white	42.000	1	32000	1
1/2	100	white	6.000	1	32021¹	1
1/2	300	white	17.100	1	32023¹	1
1/2	500	white	28.000	1	32025¹	1
1/2	1000	white	55.000	1	32020	1
3/4	100	white	11.000	1	32041¹	1
3/4	300	white	32.100	1	32043¹	1
3/4	500	white	53.000	1	32045¹	1
3/4	1000	white	106.000	1	32040²	1
1	100	white	17.000	1	32061¹	1
1	300	white	51.900	1	32063	1
1	500	white	88.000	1	32065	1

¹) center pull coil
²) Available while supplies last



ViegaPEX tubing
Zero Lead
 - PEX
 - Straight length
Technical Data
 PEX designation code 5006
 Chlorine resistance rating CL5
 UV resistance 60 days
ASTM F876, ASTM F877
Model V5003.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	white	0.540	5	33273	1
1/2	20	white	1.080	5	33020	1
3/4	10	white	1.020	5	33276	1
3/4	20	white	2.060	5	33045	1
1	20	white	3.420	5	33061	1



ViegaPEX Ultra tubing
Zero Lead
 - PEX
 - Coil
Technical Data
 PEX designation code 5306
 Chlorine resistance rating CL5
 UV resistance 6 months
ASTM F876, ASTM F877
Model V5005

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	red	21.000	1	32505	1
1/2	100	red	6.000	1	32521	1
1/2	300	red	17.100	1	32523	1
1/2	500	red	28.000	1	32525	1
1/2	1000	red	55.000	1	32520	1
3/4	100	red	11.000	1	32541	1
3/4	300	red	32.100	1	32543	1
3/4	500	red	53.000	1	32545	1
1	100	red	17.000	1	32551	1
1	300	red	51.900	1	32553	1



ViegaPEX Ultra tubing
Zero Lead
 - PEX
 - Straight length
Technical Data
 PEX designation code 5306
 Chlorine resistance rating CL5
 UV resistance 6 months
ASTM F876, ASTM F877
Model V5005.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	red	0.550	50	33529	1
1/2	20	red	1.180	50	33520	1
3/4	10	red	0.550	25	33549	1
3/4	20	red	2.020	25	33540	1
1	20	red	3.480	5	33551	1