



ViegaPEX Ultra tubing

Zero Lead

- PEX
- Coil

Technical Data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5006

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	blue	21.000	1	32605	1
1/2	100	blue	6.000	1	32621	1
1/2	300	blue	15.900	1	32623	1
1/2	500	blue	28.000	1	32625	1
1/2	1000	blue	55.000	1	32620	1
3/4	100	blue	11.000	1	32641	1
3/4	300	blue	30.900	1	32643	1
3/4	500	blue	53.000	1	32645	1
1	100	blue	17.000	1	32651	1
1	300	blue	51.900	1	32653	1



ViegaPEX Ultra tubing

Zero Lead

- PEX
- Straight length

Technical Data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5006.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	blue	0.550	50	33629	1
1/2	20	blue	1.180	50	33620	1
3/4	10	blue	0.550	25	33649	1
3/4	20	blue	2.020	25	33645	1
1	20	blue	3.480	5	33651	1



ViegaPEX Ultra tubing

Zero Lead

- For installation between studs
- PEX
- ManaPac

Components

Recycled plastic reels

Technical Data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5008

d	L [ft]	Reel(s)	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	2	red/blue	116.000	1	33300	1
3/8	500	1	blue	28.000	1	33905	1
3/8	500	1	red	28.000	1	33805	1
1/2	300	2	red/blue	48.000	1	33326	1
1/2	300	1	blue	23.100	1	33923	1
1/2	300	1	red	23.100	1	33823	1



ViegaPEX Ultra tubing

Zero Lead

- PEX
- Coil

Technical Data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5007

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	white	21.000	1	32405	1
1/2	100	white	6.000	1	32421	1
1/2	300	white	17.100	1	32423	1
1/2	500	white	28.000	1	32425	1
3/4	100	white	11.000	1	32441	1
3/4	300	white	32.100	1	32443	1
3/4	500	white	53.000	1	32445	1
1	100	white	17.000	1	32461	1
1	300	white	51.900	1	33362	1
1	500	white	88.000	1	32465	1



ViegaPEX Ultra tubing

Zero Lead

- PEX
- Straight length

Technical Data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5007.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	white	0.550	50	33429	1
1/2	20	white	1.100	50	33420	1
3/4	10	white	0.550	25	33459	1
3/4	20	white	2.100	25	33405	1
1	20	white	3.480	5	33461	1