



Viega ProPress adapter
Smart Connect technology
 - For use with ASTM B88 and B75 tubing
 - Copper
 - Press connection, female pipe thread

Components

EPDM sealing element

Note

Must be installed with Viega ProPress XL-C rings and V2 actuator.

Model 0912XL

P	FPT	Wt [lb]	Quantity	Part No	DG
2½	2½	1.821	1	20819	8
3	3	2.923	1	20829	8
4	4	4.404	1	20839	8



Viega ProPress adapter
Zero Lead
 - For use with Viega ProPress fittings
 - Bronze
 - Street, female pipe thread

Model 2912.1ZL

FTG (CTS)	FPT	Wt [lb]	Quantity	Part No	DG
½	¾	0.069	5	79425	8
½	½	0.102	5	79430	8
½	¾	0.140	5	79435	8
¾	½	0.111	5	79440	8
¾	¾	0.148	5	79445	8
1	½	0.172	1	79455	8
1	1	0.262	1	79450	8
1¼	½	0.267	1	79460	8
1¼	1¼	0.402	1	79465	8
1½	1½	0.519	1	79470	8
2	2	0.825	1	79475	8

Flanges



Viega ProPress adapter flange
2 - pc
Smart Connect technology
Zero Lead
 - For use with ASTM B88 and B75 tubing
 - Bronze
 - Press connection

Components

EPDM sealing element

Model 2959.5ZL

P	BP	BPd	Wt [lb]	Quantity	Part No	DG
1	4	3½	3.292	1	79680	8
1¼	4	3½	3.196	1	79685	8
1½	4	3¾	4.069	1	79690	8
2	4	4¾	5.867	1	79695	8

BP = bolt pattern
 BPd = bolt pattern diameter



Viega ProPress adapter flange
2 - pc
Smart Connect technology
 - For use with ASTM B88 and B75 tubing
 - Copper
 - Press connection

Components

EPDM sealing element

Note

Must be installed with Viega ProPress XL-C rings and V2 actuator.

Model 0959.5XL

P	BP	BPd	Wt [lb]	Quantity	Part No	DG
2½	4	5½	6.762	1	20853	8
3	4	6	8.309	1	20858	8
4	8	7½	11.835	1	20863	8

BP = bolt pattern
 BPd = bolt pattern diameter

Caps



Viega ProPress cap
Smart Connect technology
 - For use with ASTM B88 and B75 tubing
 - Copper
 - Press connection

Components

EPDM sealing element

Model 2956

P	Wt [lb]	Quantity	Part No	DG
½	0.057	10	77712	8
¾	0.088	10	77717	8
1	0.122	5	77722	8
1¼	0.174	1	77727	8
1½	0.331	1	77732	8
2	0.431	1	77737	8